

THE IMAGE OF OUALITY

RONIX® IP & Analog Surveillance Camera ALITY Test Monitor & Installation Tool

Features:

- 7 inch LCD touch screen 1024×600
- · ONVIF IP camera test
- Test H.264/MPEG4/MJPEG IP cameras
- Built in Wi-Fi can receive images from wireless cameras as well as ONVIF and customized IP cameras
- · HDMI signal output, supports 1080p
- Analog camera image display, auto adapts and display NTSC or PAL video formats
- Supports more than 30 protocols such as PELCO-P, PELCO-D, SAMSUNG etc
- · Video image magnification enables detailed viewing
- Snapshot and save images as JPG files in an SD card, video record and playback
- · LED Lamp, easy to operate at night
- · Removable micro SD card
- · LCD screen with brightness/contrast/color saturation adjustment
- · PoE voltage test
- · Audio input and output test
- · DC12V 2A output to power cameras
- PoE power output, supplies temporary power for PoE cameras
- Supports RS232/RS485, Rate 600 115,200bps adjustable
- · Enhanced Color bar generator, video generator, eight-system switchable, transmit/receive eight-system colorful images
- · PEAK video signal level, SYNC signal level, Color burst chroma level measurement & test video signal attenuation
- · Cable tracing by sending an audio signal, enables the blue cable tracer tester to find the connected cable bundles
- · Ping test for testing connected IP cameras or other network equipment's Ethernet port function and to determine if the IP address is correct
- · Quick search for the connected IP camera or other network device's IP address
- · Cable test, Test LAN cable, telephone cable or UTP cable, cable type and the sequence of wires will be displayed
- PTZ protocol analysis, control protocol command displays to check RS485 transmission
- · PTZ control, Pan/tilts the P/T unit, zooms lens in and out, adjusts the focus, aperture and sets preset positions
- 7.4V 48.1Wh Battery energy display, Lithium Ion Polymer Battery can last 16 hours of normal use after charging for 8 hours
- · 2 Year Limited Warranty

Description:

The ST-IP-TEST 7 inch touch screen IP camera tester is designed for maintenance and installation of both IP cameras and analog cameras as well as other security equipment. It's 1024 x 600 resolution enables it to display images from network HD cameras and analog cameras in top quality. The unit supports both ONVIF PTZ and analog PTZ control. A combination of touch screen and push buttons make the IP camera tester very user friendly. In addition the tester is also a great tool for Ethernet networks and cabling systems. It can test PoE voltage and is capable of IP address searching. It can diagnose the location of a coaxial cable or network cable's short circuit and open circuit.

Through audio signal generation the blue cable tracer tester can find connected cables from unorganized or unlabeled cable bundles and includes the ability to test LAN cable or telephone cable types while verifying the sequence of the individual conductors. Other functions include 24W PoE power supply, LED Lamp and DC 12V 2A power output. The meters portability, user-friendly design and multi-function capability make it an essential tool for installers and technicians, greatly improving work efficiency and simplifying installations and system maintenance.

Ordering Information:

ST-IP-TEST IP Buddy+ IP & Analog Surveillance

Camera Test Monitor & Installation

Tool

ST-IP-TEST-BATTERY Replacement Battery

ST-IP-TEST-PS Replacement AC Charger

ST-IP-TEST-SP Screen Protector for ST-IP-TEST

Meter, Pack of 3



Contents Include:

1 CCTV Test Meter

Instruction Manual

1 Carrying Case

Carrying Strap for Case

1 Carrying Strap for Meter

I AC Charger

1 Test Probe

BNC to Alligator Clip Cable

1 3.5mm to Alligator Clip Cable

1 2 Conductor Screw Terminal to

Alligator Clip Cable

1 BNC Male to BNC Male Jumper Cable

DC to DC Jumper Cable

North American Cable Equipment Inc. (800) 688-9282 Fax: (800) 230-1793 email: sales@securitytronix.com web: www.securitytronix.com www.northamericancable.com