



## **AXIS Washer Kit A**

## For clear vision all year round

AXIS Washer Kit A sprays cleaning fluid on the windows of AXIS Q86 PT Head Network Camera Series. The kit contains a 23 liter (6 gallon) tank, a pump for delivery up to 11 m (36 ft), a tube, a nozzle and a mounting bracket for attaching the nozzle to the PT-head, which must be installed between the mount and the base unit.

- > Spray cleaning fluid
- > Elevation 11 m
- > Tank capacity of 23 l (6 gal)
- > Suitable for AXIS Q86 Series





## **AXIS Washer Kit A**

General	
Supported cameras	AXIS Q86 PT Head Network Camera Series
Casing	Tank: Polyethylene Cage: Stainless steel Electronics enclosure: Technopolymer Nozzle bracket*: Stainless steel *The nozzle bracket must be installed between the mount and the base unit.
Dimensions	301 x 410 x 348 mm (11.8 x 16.1 x 13.7 in)
Weight	6.7 kg (14.8 lb)
Power	230 V AC, 0.5 A, 50/60 Hz 120 V AC, 1 A, 50/60 Hz 12 V AC, 3.8 A, 50/60 Hz
Tank capacity	23 l (6 gal)
Delivery head	Plastic covered copper pipe with stainless steel nozzle
Tube length	11 m (36 ft)
Elevation	11 m 1 m/sec

Operating conditions	Antifreeze liquid in solution, full performance: $-10~^{\circ}\text{C}$ to $60~^{\circ}\text{C}$ (14 $^{\circ}\text{F}$ to 140 $^{\circ}\text{F}$ ) Antifreeze liquid in solution, reduced performance due to higher fluid viscosity at lower temperatures: $-25~^{\circ}\text{C}$ to $60~^{\circ}\text{C}$ ( $-13~^{\circ}\text{F}$ to $140~^{\circ}\text{F}$ )
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Approvals	EN 50130-4 EN 61000-6-3 FCC Part 15 Subpart B Class B VCCI Class B EN 60950-1 EN 60950-22 EN 60529 IP56 EAC Certification
Included accessories	Installation Guide
Warranty	Axis 3-year warranty, see www.axis.com/warranty

More information is available at www.axis.com

