

# IR Megapixel Vari-focal Bullet

## 1.3MP Bullet Network Camera



- Max 30fps@1.3MP (1280×960) & 30fps@720p (1280×720)
- DWDR
- True Day/Night
- Motorized Lens 2.7mm-12mm
- Smart IR 30m (98ft)
- Outdoor Rated IP67
- Onboard Storage



### System Overview

The IR Megapixel Vari-focal bullet camera delivers 1.3MP resolution with a motorized 2.7mm – 12mm varifocal lens. The camera's elegant blend of aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

### Functions

#### True Day/Night

A day/night mechanical IR cut filter makes this camera ideal for applications with fluctuating lighting conditions, delivering color images during the day and automatically switching to monochrome as the scene darkens.

#### Regions of Interest

Regions of Interest (ROI) is a user defined feature that allows the operator to monitor specific areas of a scene while still maintaining overall situational awareness of less important areas.

#### Smart IR

With IR illumination, the camera has the ability to capture detailed images in low light or total darkness. The camera's Smart IR technology adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object. Smart IR technology prevents IR LEDs from whiting out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 30m (98ft).

#### Motorized Lens

With a motorized lens, focusing the camera is quick and convenient for both the initial installation and future adjustments. Simply install the camera, dial in the lens, and then make adjustments from the convenience of your computer. For sites that require lens adjustments, remote focus eliminates the hassle of driving to the site deploying a ladder, or spending time away from the office.

### Image Flip

Capturing unnecessary data such as surrounding hallway walls can increase storage requirements without any added value. The image flip feature allows the camera's image to be rotated in 90° increments for better video optimization.

### Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust to IP67 standards, making it suitable for indoor or outdoor environments.

Supporting ±25% input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 8KV lightning rating provides protection against the camera and its structure from the effects of lightning.

### Streaming

With a choice of unicast or multicast streaming, bandwidth-efficient viewing, recording and third-party video management can easily be achieved. Dual streaming enables bandwidth-efficient viewing and recording. Depending on the resolution and frame rate selected on the first stream, the second stream provides a copy at a lower resolution.

### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) and PSIA (Physical Security Interoperability Alliance) specifications, ensuring interoperability between network video products regardless of manufacturer.

## Camera

Lens

## Pan/Tilt/Rotation

## Video

## Network

## Certifications

www.dahuasecurity.com/en/us  
Available from A1 Security Cameras  
www.a1securitycameras.com email: sales@a1securitycameras.com

# Lite Series | DH-IPC-HFW21A0RN-ZS

## Electrical

<b>Power Supply</b>	12V DC $\pm$ 25%, PoE (af Class 0)
<b>Power Consumption</b>	Max. 7.5W (12V DC, IR On), Max. 7.5W (PoE, IR On)

## Environmental

<b>Operating Conditions</b>	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
<b>Storage Conditions</b>	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
<b>Ingress Protection</b>	IP67

## Construction

<b>Casing</b>	Metal
<b>Dimensions</b>	72mm $\times$ 80mm $\times$ 212.8mm (2.8" $\times$ 3.1" $\times$ 8.4")
<b>Net Weight</b>	0.40Kg (0.88lb)
<b>Gross Weight</b>	0.65Kg (1.43lb)

## Ordering Information

Type	Part Number	Description
1.3MP Camera	DH-IPC-HFW21A0RN-ZS	1.3MP, 2.7mm-12mm, True D/N, DWDR, 30fps@1.3MP, 30fps@720p, IP67, IR: up to 30m (98ft), DC12V, PoE
Accessories	PFA135	Junction Box
	PFA150	Pole Mount Bracket

## Accessories

Optional:



Junction Mount	Pole Mount
PFA135	PFA135+PFA150

## Dimensions (mm/inch)

