



## FD8179-H

Fixed Dome Network Camera

4MP · 30M IR · WDR Pro · Smart Stream II · 3DNR · Defog

VIVOTEK FD8179-H is an indoor stylish-design 4-Megapixel IR fixed dome camera offering superb video quality with up to 30 fps at 2688x1520. This all-in-one camera with WDR Pro technology (supports up to 3.6MP, 24 fps @ 2560x1440) and a fixed 2.8 mm lens is capable of capturing high visibility in high contrast environments.

By adopting with VIVOTEK's sophisticated Smart Stream II technology, the FD8179-H can optimize image quality for desired regions, and thus ensure maximum efficiency of bandwidth usage and savings of up to 50% on bandwidth and storage requirements.

As a day/night easy-to-use camera, the FD8179-H features a removable IR-cut filter as well as IR illuminators effective up to 30 meters for superior image quality. For making the camera adaptable any indoor surveillance, the FD8179-H comes with a number of features such as video rotation, defog, a dedicated MicroSD/SDHC/SDXC card slot, and VIVOTEK's 32-channel recording software.

### Key Features

- 4-Megapixel CMOS Sensor
- 30 fps @ 2688x1520
- Real-time H.264, MJPEG Compression (Dual Codec)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 30 Meters
- Smart IR Technology to Avoid Overexposure
- WDR Pro for Unparalleled Visibility in Extremely Bright and Dark Environments (supports up to 3.6MP, 24 fps @ 2560x1440)
- Smart Stream II to Optimize Bandwidth Efficiency
- 3D Noise Reduction
- Built-in 802.3af Compliant PoE
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage
- Supports ONVIF Standard to Simplify Integration and Enhance Interoperability

## Technical Specifications

Model	FD8179-H	Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS
<b>System Information</b>		Interface	10 Base-T/100 BaseTX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
CPU	Multimedia SoC (System-on-Chip)	ONVIF	Supported, specification available at <a href="http://www.onvif.org">www.onvif.org</a>
Flash	128MB	<b>Intelligent Video</b>	
RAM	256MB	Video Motion Detection	Five-window video motion detection
<b>Camera Features</b>		<b>Alarm and Event</b>	
Image Sensor	1/3" progressive CMOS	Alarm Triggers	Motion detection, manual trigger, periodical trigger, system boot, recording notification, camera tampering detection
Maximum Resolution	2688x1520 (4MP)	Alarm Events	Event notification using HTTP, SMTP, FTP, NAS server and SD Card File upload via HTTP, SMTP, FTP, NAS server and SD card
Lens Type	Fixed-focal	<b>General</b>	
Focal Length	f = 2.8 mm	Connectors	RJ-45 for Network/PoE connection
Aperture	F1.8	LED Indicator	System power and status indicator
Field of View	114° (H) 61° (V) 132° (D)	Power Input	IEEE 802.3af PoE Class 0
Shutter Time	1/5 sec. to 1/16,000 sec.	Power Consumption	Max. 10 W
WDR Technology	WDR Pro (supports up to 3.6MP, 24 fps @ 2560x1440)	Dimensions	Ø 129 x 94 mm
Day/Night	Removable IR-cut filter for day & night function	Weight	Net: 416.4 g
Minimum Illumination	0.14 Lux @ F1.8 (Color) 0.01 Lux @ F1.8 (B/W)	Safety Certifications	CE, LVD, FCC Class B, VCCI, C-Tick, UL
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in)	Operating Temperature	Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F)
IR Illuminators	Built-in IR illuminators, effective up to 30 meters with Smart IR IR LED*8	Humidity	90%
On-board Storage	Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording	Warranty	24 months
<b>Video</b>		<b>System Requirements</b>	
Compression	H.264 & MJPEG	Operating System	Microsoft Windows 8/7/Vista/XP/2000
Maximum Frame Rate	30 fps @ 2688x1520 (without WDR Pro) 24 fps @ 2560x1440	Web Browser	Mozilla Firefox 7~43 (streaming only) Internet Explorer 7/8/9/10/11
Maximum Streams	3 simultaneous streams	Other Players	VLC: 1.1.11 or above QuickTime: 7 or above
S/N Ratio	61.8dB	<b>Included Accessories</b>	
Dynamic Range	110dB	Others	Quick installation guide, alignment sticker, screw pack
Video Streaming	Adjustable resolution, quality and bitrate; Smart Stream II	<b>Dimensions</b>	
Image Settings	Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings, 3D noise reduction, video rotation, defog		
<b>Audio</b>			
Audio Capability	Audio input		
Compression	G.711, G.726		
Interface	Build-in microphone		
Effective Range	5 meters		
<b>Network</b>			
Users	Live viewing for up to 10 clients		

## Compatible Accessories

### Mounting Kits



**AM-21A**  
L-shape Bracket



**AM-51D**  
Adapter Ring



**AM-528**  
Mounting Adapter