



**VERTILINE**  
VertiLine33D

### **Overview**

Vertiline33D Rack Mount DC Power Supply provides sixteen (16) filtered and electronically regulated power outputs in a space saving 1U EIA 19" rack mount chassis. Vertiline Rack Mount Power Supplies are also available in 24VDC and eight (8) outputs configurations.

### **Specifications**

#### ***Input:***

- 115VAC 60 Hz, 1.5 amp input.

#### ***Output:***

- 12VDC outputs rated @ 8 amp total current max. (0.5 amp per device, 2.5 amp max.).
- Sixteen (16) PTC protected power outputs.
- Filtered and electronically regulated.

#### ***Electrical:***

- Operating temperature: -20° C to 49° C ambient.
- 49.13 BTU/Hr.
- System AC input VA requirement: 172.5VA.

#### ***Features:***

- Sixteen (16) power LEDs.

#### ***Features (cont'd):***

- Illuminated master power disconnect circuit breaker with manual reset.
- IEC 320 - 3-wire grounded line cord (detachable).
- Removable terminal blocks with locking screw flange.

#### ***Mechanical:***

- Units can be rack, wall or shelf mounted.
- Modular 1U standard EIA 19" rack mount chassis.
- Enclosure Dimensions (H x W x D approx.): 1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm).
- Product weight (approx.): 7.2 lbs. (3.27 kg).
- Shipping weight (approx.): 8.3 lbs. (3.76 kg).

### **Agency Approvals**



European Conformity

**A1 SECURITYCAMERAS**  
**The First Name in Security**  
**Enclosure Dimensions (All are approximate):**  
**1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)**

