


## HD-TVI 2MP IR Dome Camera

**VLD2TW** 3.6mm fixed lens, white housing

### Features

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30 fps
- Full OSD operation through on-board control and UTC (up the coax)
- 24 built-in IR LEDs
- 3 axis lens mount
- Adapter plate in optional accessories included
- Additional analog output for 960H
- Signal distance up to 1600 ft.<sup>1</sup>
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty<sup>2</sup>



### Specifications

Image Sensor ..... 1/3" 2MP CMOS  
Resolution..... 1080p/720p  
Minimum Illumination..... 0 lux @F2.0 (IR on) / 0.1 lux @F2.0 (IR off)  
S/N Ratio ..... 50dB  
Motion Detection..... Yes  
Day/Night..... IR-cut filter  
DNR..... 2D/3D Automatic  
Number of IR LEDs ..... 24  
IR Range ..... 32' (depending on scene reflection)  
Power Supply ..... 12VDC (power supply not included)  
Power Consumption ..... 400mA (IR on)  
Operating Temperature..... -4° F - 104° F  
Weight ..... 1.1 lbs.  
Dimensions..... 4.5" (Dia.) x 5" (H)

### Optional Accessories



**INTPMW**  
Pendant  
Mount



**INTWMW**  
Dome Wall  
Mount



**INTCMW**  
Corner/Pole  
Adapter  
(use with INTWM)



**CVCJBDW**  
Small Round  
Junction Box



**PSW5**  
12VDC  
Power Supply



**TVIUTPPT**  
HD Video  
Transceiver with  
Pigtail (Balun)



**TVIUPT**  
HD Video  
Transceiver

<sup>1</sup>To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield.

<sup>2</sup>Effective on all new purchases as of 2/1/17. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/6/17