

LTD2708TS-M

1080P TVI DVR



Key Features

- 8 CH HD TVI video input
- 8CH 1080P or 720p@ 30fps live preview
- 8CH 1080P@ 15fps or 720P@ 30fps recording
- 1080P and 720P signal auto detect
- Long transmission distance over coax cable
- 8 CH simultaneously playback

Rear Panel



1. Audio in
2. Audio out
3. HD-TVI Video in
4. HDMI Interface
5. VGA Interface
6. LAN
7. USB
8. DC 12V
9. RS-485 Serial Interface

LTD2708TS-M	
Video / Audio input	
Video compression	H.264
Video input	8ch BNC (1.0 Vp-p, 75Ω)
Audio compression	G.711u
Audio input	1-ch, RCA(2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Video / Audio output	
HDMI output	1-ch, resolution: 1920×1080 /60 Hz
VGA output	1-ch, resolution: 1920x1080,1280x1024, 1024x768, 800x600/60HZ
Audio output	1-ch, RCA
Audio bit rate	64 Kbps
Recording and Playback	
Video bit rate	1M-6Mbps
Encoding resolution	1080P: 15fps(NTSC)/12fps(PAL) 720P:30fps(NTSC)/25fps(PAL);
Decoding resolution	1080P: 15fps(NTSC)/12fps(PAL) 720P:30fps(NTSC)/25fps(PAL);
Dual-stream	YES
Synchronous playback	8-ch
Hard disk	
SATA	1 SATA interfaces
Capacity	Up to 6TB capacity for each disk
External interface	
Network interface	1, RJ45 10M / 100M Ethernet interface
RS485	1 RS485, connect to PTZ or keyboard
USB interface	2, USB2.0
Alarm in	NO
Alarm out	NO
General	
Power supply	DV12V
Power Consumption	≤10W (without hard disk)
Working temperature	-10 °C ~ + 55 °C(14 °F - 122°F)
Working humidity	10% ~ 90%
Chassis	compact 1U chassis
Dimension	300mm x 270mm x 58 mm
Weight	≤ 2kg(4.4lb) (without hard disk)