


HD-TVI 2MP IR Dome Camera

VLD1TW 2.8-12mm auto iris varifocal lens, white housing

Features

- Full HD resolution over coax (HD-TVI)
- Full OSD operation through on-board control and UTC (up the coax)
- 30 built-in IR LEDs
- Supports up to Full HD 1080p @30fps
- 3 axis lens mount
- Adapter plate for optional accessories included
- Additional BNC output for 960H analog
- Signal distance up to 1600 ft.¹
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty²



Specifications

Image Sensor 1/3" 2MP CMOS
 Resolution..... 1080p / 720p
 Minimum Illumination..... 0 lux (IR on)
 S/N Ratio more than 52dB
 Motion Detection..... Yes
 Day/Night..... IR-cut filter
 DNR..... 2D/3D Automatic
 Number of IR LEDs 30
 IR Range 100' (depending on scene reflection)
 Power Supply 12VDC (power supply not included)
 Power Consumption 400mA (IR on)
 Operating Temperature..... -4° F - 104° F
 Weight 2.1 lbs.
 Dimensions..... 5.7" (Dia.) x 4.5" (H)

Optional Accessories



O4JBD
Junction Box



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUPT
HD Video
Transceiver

¹To preserve signal quality and distance, Speco Technologies recommends using coax with a 100% copper center conductor and at least 95% braided copper shield.

²Effective on all new purchases as of 2/1/17. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/6/17