


Platinum 4.1MP Network Mini Wifi Dome Camera CMIP3142W-28SWIFI



Key Features:

- 4.1MP High Definition
- True 120dB Wide Dynamic Range
- 3D DNR,BLC,Intelligent H.264 Zip+
- Built-in microphone, Audio Output, Alarm I/O
- IP67, Vandal-proof
- Support Wifi
- DC 12V/ PoE

Dimensions:



Unit: mm

WDR
120dB



Platinum 4.1MP Network Mini Wifi Dome Camera

CMIP3142W-28SWIFI

CAMERA	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/10,000 s
Lens	2.8mm, Angle of view: 106 °
Lens Mount	M12
Day & Night	IR cut filter with auto switch
DNR	3D DNR
Wide Dynamic Range	120dB
Angle Adjustment	Pan: -30 ° ~ 30 °, Tilt: 0 ~ 75 °, Rotation: 0 ~ 360 °
Compression Standard	
Video Compression	H.264 / MJPEG/H.264 Zip+
H.264 Type	Main Profile
Video Bit Rate	32 Kbps ~16Mbps
Dual streams	Support
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit rate	64Kbps (G.711) / 16Kbps (G.722.1) / 16Kbps (G.726) / 32-128Kbps (MP2L2)
Image	
Max. Resolution	2688×1520
Frame Rate	60Hz: 20fps (2688×1520), 30fps (1920×1080), 30fps (1280×720) 50Hz: 20fps (2688×1520), 25fps (1920×1080), 25fps (1280×720)
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser
BLC	Support, zone configurable
ROI Codec	Support
Network	
Network Storage	NAS (Support NFS, SMB/CIFS), ANR
Alarm Trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
General	One-key reset, Flash-prevention, dual stream, heartbeat, mirror, password protection, privacy mask, watermark, IP address filtering, Anonymous access
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
Interface	
Communication Interface	1 RJ45 10M/100M Ethernet port
On-board storage	Built-in Micro SD/SD HC/SDXC slot, up to 128GB
Alarm interface	1x alarm I/O
Audio interface	Built-in microphone and 1x audio output
Reset	Yes

Platinum 4.1MP Network Mini Wifi Dome Camera

CMIP3142W-28SWIFI

Wi-Fi	
Wireless Standards	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	20/40MHz Support
Protocols	802.11b: CCK, QPSK, BPSK, 802.11g/n: OFDM
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Transfer Rates	11b: 11Mbps, 11g: 54Mbps, 11n: up to 150Mbps
Wireless Range	50 meters *The performance varies based on actual environment.
General	
Working Temperature /Humidity	-22 °F ~ 140° F (-30° C~ 60 °C) Humidity 95% or less (non-condensing)
Power Supply	DC12V ±25%, PoE (802.3af)
Power Consumption	Max. 5W
IR Range	Approx. 33ft (10 meters)
Material	Top Cover: Plastic ; Base: Metal
Weather Proof Ratings	IP67
Impact Protection	IEC60068-275Eh, 20J; EN50102, up to IK08
Dimensions	3.9" ×3.8" ×2.1" (99.3×96.7×52.8 mm)
Weight	1.32 lbs (600 g)