

16 Channel Color Duplex Multiplexer

RMX16CD

Features

- View up to 16 image sources on one screen while simultaneously recording full screen images on a DVR or VCR
- Full-screen and multi-screen viewing options are available during VCR playback
- Uniquely programmable for recording between 2 999 hours
- Built-in time/date generator
- 8 Character camera title function
- · Video loss alert and alarm detection are structured
- Compatible with all standard time lapse VCRs and most DVRs
- 4 Channel color (RMX4CD) and 9 channel color (RMX9CD) models are also available



Specifications

•	
Camera Inputs	. BNC, 16, composite video 1.0Vp-p 75 ohms
Adjustable Program Recording	. 2-999 hours-accepts trigger pulses from VCRs & DVRs
Alarm Functions	. Video loss alert and alarm detection with up to 100 record
Alarm Inputs	. 16 (TTL level)
Alarm Output	. 1, Normally open or closed (relay output) contacts with shared common
Compatibility	. Compatible with all standard and time lapse VCRs and most DVRs
Looping Camera Outputs	. BNC, 16, composite video 1.0Vp-p 75 ohms
Maximum Image Sources	. 16 on one screen
Monitor Output	. BNC, 1, composite video 1.0Vp-p 75 ohms
Other Features	. Built-in time and date generator with 8 character camera title function
Playback Input	. BNC, 1, composite video 1.0Vp-p 75 ohms
Power Consumption	. Maximum 9 watts
Power Source	. 12VDC, 1.2 amp included
Recovery Output	. 1 (TTL active low)
RS-232 Interface	. D-SUB 25 pin female connector
Switch Input	. BNC, 1 (TTL level)
VCR Output	. BNC, 1, composite video 1.0Vp-p 75 ohms
VCR Input	. BNC, 1, composite video 1.0Vp-p 75 ohms
Viewing Options	. Full screen, multi-screen or sequential switching with adjustable dwell time
Dimensions	. 1.75" (H) x 17" (W) x 9.75" (D)
Weight	. 5 lbs. 8 oz. net

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/3/15