

## AXIS T91H61 Wall Mount

Quick connection and room for more

Designed for fixed dome cameras, AXIS T91H61 Wall Mount accommodates and safely protects accessories inside the mount. Connect to power and data quickly and easily with the built-in RJ45 cable and connection. Designed to be impact- and weather-resistant, this mount is suitable for all environments both indoors and outdoors. It can be mounted on poles and corners with the help of optional accessories.

- > Room for connectivity devices, midspans (not included) and service loop
- > Protection against impacts, rain, dust and corrosion
- > Built-in RJ45 cable with connector



## AXIS T91H61 Wall Mount

### General

<b>General</b>		IEC 60068-2-6 (Sinus)
<b>Supported products</b>	All camera pendant kits with 1.5" NPS thread mount, such as: AXIS P32-VE cameras (requires camera specific pendant kit) AXIS P33-VE cameras (requires camera specific pendant kit) AXIS Q35-VE cameras (requires camera specific pendant kit) AXIS Q36-VE cameras (requires camera specific pendant kit) AXIS P3707-PE camera (requires camera specific pendant kit) For a complete list of compatible cameras, please visit: <a href="http://www.axis.com/se/sv/products/accessory-selector">http://www.axis.com/se/sv/products/accessory-selector</a>	IEC 60068-2-27 (Shock) UL 50E MIL-STD 810G 509.5
<b>Casing</b>	Material: Powder coated aluminum casing Color: White NCS S 1002-B	<b>Included accessories</b>
<b>Dimensions</b>	185 x 214 x 404 mm (7.28 x 8.43 x 15.9 in)	Installation guide Ethernet cable with male-to-male RJ45 connectors (with gasket C M20) Foam gaskets and silicone strap (pre-mounted) Cable ties
<b>Weight</b>	3.9 kg (8.6 lb)	<b>Optional accessories</b>
<b>Maximum load</b>	30 kg (66 lb)	AXIS T8120 Midspan 15 W 1-port AXIS T81B22 DC 30 W Midspan 1-port <sup>a</sup> AXIS T8133 30 W Midspan <sup>a</sup> AXIS T8642 PoE+ over Coax Device AXIS T91A57 Pole Mount AXIS T91A64 Corner Mount AXIS ACI Conduit Adapters Network cable coupler indoor slim For more accessories, see <a href="http://www.axis.com">www.axis.com</a>
<b>Cable routing</b>	Back: Cable hole Bottom: 3/4" Conduit entrance x2	<b>Warranty</b>
<b>Environment</b>	Indoor Outdoor	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>
<b>Approvals</b>	IEC/EN/UL 60950-1 IEC/EN/UL 60950-22 EN 50581 IEC/EN 60529 IP66 NEMA 250 Type 4X IEC 62262 IK10	<b>a. Midspan not included</b>  <b>Environmental responsibility:</b>  <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>

a. *Midspan not included*

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)