

P1MM

Small Form-Factor Pluggable (SFP)

Multi-Mode Transceiver

Description

Altronix P1MM module allows for an optical or electrical interface when using a managed switch, unmanaged switch or media converter. This hot-pluggable SFP module can be used with multi-mode optical fiber.



P1MM

Key Features

- IEEE 802.3a compliant.
- Spans distances up to 550m (1804 ft.)
- Conforms to (SFP) Small Form-Factor Pluggable Multi-Source Agreement (MSA).

P1MM Specifications

Altronix Model Number	Rate (bps)	Wave (nm)	TX power (dBm)	RX Sensitivity (dBm)	Maximum Length	Temp. (°C)
P1MM	1.25G	850	-18~0	-8~-4	550m	0° to 70°

Specifications

Standards

Class 1 FDA and IEC60825-1 Laser Safety Compliant.
Compliant with MSA SFP Specification.

Connector Type

LC Duplex.

Data Rate

Up to 1.25Gbps.

Wave

850nm VCESL Laser Transmitter.

Distance

550m with 50/125 µm MMF.

Agency Listings

FCC FCC Compliant
CE European Conformity.
ROHS

Physical and Environmental

Dimensions (L x W x H)

2.25" x 0.5" x 0.625" (57.15mm x 12.7mm x 15.875mm).

Weight (approx.)

Product Weight: 0.00625 lbs. (0.003 kg).
Shipping Weight: 0.09375 lbs. (0.042 kg).

Temperature

Operating: 0°C to 70°C (32°F to 113°F).
Storage: -40°C to 85°C (-40°F to 185°F).

Relative Humidity 85% +/-5%.