

DTMR1

Single Channel Annual Event Timer

Description

Altronix DTMR1 programmable timer is suitable for many functions that require a timed operation e.g. Access Control Applications, Siren/Bell Cut Off Module, Dialer Delay, Guard Tour Supervisory Timer, etc. Some optional functions include: One Shot, Delayed Release, Delayed Operate, Delayed Pulse and Pulsar/Flasher. A new feature has been added which provides a momentary relay activation at the end of a desired timing cycle. This feature eliminates the need for having to use two (2) timers to achieve this function. Another new feature will cancel (interrupt) timing cycle and reset timer if desired.



DTMR1

Key Features

- Quick and extremely accurate time range adjustment from 1 sec. to 60 min.
- Triggers via positive DC (+) voltage, dry contact closure or removal of contact closure.
- Selectable relay activation at the start or end of the timing cycle.
- One (1) second momentary relay activation at the end of the timing cycle eliminates the need to use two timers for this function.
- Built-in reset feature which cancels timing cycle.
- Repeat (pulsar/flasher) mode.

Specifications

Input

Voltage 12 or 24 VDC selectable.

Relay

Form "C" relay contacts are 8A at 120VAC/28VDC.
Current Draw: Stand-by 3mA; Relay Energized 40mA.

Indicator (LED)

Relay is energized.

Physical and Environmental

Dimensions (L x W x H)

3" x 2.5" x 0.75" (76.2 mm x 63.5 mm x 19.05 mm).

Product Weight 0.2 lbs. (0.09 kg).

Shipping Weight 0.25 lbs. (0.11 kg).

Temperature

Operating -20°C to 49°C (-4°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

Accessories:



ST3

ST3 - Snap Track (included)

Designed for mounting Altronix products to Din Rail without the use of mounting screws.



D10

D10 - Din Rail (order separately)

10" metal rail for mounting circuit boards and/or power supplies and peripherals inside equipment racks or enclosures.