

ALTV615DC1016 Series DC CCTV Power Supplies

Description

Altronix ALTV615DC1016 Series power supplies are designed with sixteen (16) individual fuse or PTC protected outputs for powering CCTV cameras and other video accessories. They provide 6VDC-15VDC with a total of up to 10A continuous supply current.



ALTV615DC1016

Key Features

- Sixteen (16) fuse or PTC protected outputs.
- 6-15VDC field adjustable output voltage.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.
- AC Input and DC Output LED indicators.
- Spare fuses provided.
- Lifetime Warranty / Made in the U.S.A.

ALTV615DC1016 Series Power Supply Configuration Reference Chart

Altronix Model Number	Total Output Current (Power)	Output Voltage	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max. per output)	115VAC 50/60Hz Input Current
ALTV615DC1016	10A	6-15VDC	16	—	✓	3.5A	1.9A
ALTV615DC1016CB				✓	—	2.5A	

Specifications

Input

Voltage 115VAC, 50/60Hz, 1.9A.

Outputs

Voltage 6-15VDC.
Current Up to 10A.

Indicators (LED)

Input LED.
Output LED.

Physical and Environmental

Dimensions (H x W x D):

13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

Weight:

Product Weight 14.9 lbs. (6.76 kg).
Shipping Weight 16.2 lbs. (7.35 kg).

Temperature:

Operating 0°C to 49°C (32°F to 120°F).
Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr. (approx.): 31-77 BTU/Hr., depending on output.