


Platinum HD-TVI Dome Camera 3MP CMHD73T2-28



Key Features:

- 3MP High Definition
- 2.8mm Fixed Lens
- 2 Matrix IR up to 65ft(20m)
- DC 12V
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

Dimensions:



Platinum HD-TVI Dome Camera 3.1MP

CMHD73T2-28

CAMERA

Image Sensor	1/3"CMOS
Signal System	NTSC/PAL
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Lens	2.8mm
Shutter Speed	1/30(1/25) s to 1/50,000 s
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1920x1536@18fps
HD Video Output	1 HD-TVI Output
S/N Ratio	More than 62dB

MENU

AGC	Support
D/N Mode	Color/ BW/ SMART
White Balance	ATW/ MWB
BLC	Support
Function	DNR, Mirror, SMART IR

GENERAL

Working Temperature	-40 ° F - 140 ° F (-40° C - 60 ° C)
/Humidity	Humidity 90% or less (non-condensing)
Power Supply	DC 12V
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 65ft(20m)
Impact Protection	IK10
Dimension	4.4 "×3.3" (111.0×82.5 mm)
Weight	0.8lb(350g)