

**eFlow6N Series  
Power Supply/Chargers**

**Description**

Altronix eFlow6N series power supply/chargers convert a 120VAC 60Hz input into a single, eight (8) or sixteen (16) fused outputs or PTC protected Class 2 power-limited outputs. Outputs are selectable for 12VDC or 24VDC with a total of 6A max. supply current. It also offers a suite of features that includes fire alarm disconnect, overvoltage protection, and low power disconnect which prevents deep discharge of stand-by batteries.



eFlow6N8

**Key Features**

- Available with 1, 8 or 16 outputs.
- Fused outputs or PTC protected Class 2 power-limited outputs.
- Additional aux. Class 2 power-limited output rated @ 1A.
- Overvoltage protection.
- Fire alarm disconnect.
- Supervision
  - AC Fail
  - Battery Fail and Battery Presence
  - Low power shutdown.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- Short circuit and overload protection.
- AC input and DC output indicators.
- UL Listed in the U.S. and Canada.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

**eFlow6N series Power Supply Configuration Reference Chart**

Altronix Model Number	Nominal DC Outputs				Maximum Supply Current for Main and Aux. Outputs (A)	Input Rating: 120VAC, 60Hz	Input Fuse Rating	Battery Fuse Rating	Ripple Voltage (mV) Under low battery condition	Power Distribution Module(s)	Number of Outputs	Fused Outputs Ratings	Auto-Resettable PTC Outputs Ratings	Accommodates up to 7AH Batteries	Accommodates up to 12AH Batteries
	[DC]		[AUX]												
	12VDC Output Range (volts)	24VDC Output Range (volts)	12VDC Output Range (volts)	24VDC Output Range (volts)											
eFlow6N	10.0-13.2	20.19-26.4	10.03-13.2	20.19-26.4	6A	3.5A	5A/250V	10A/32V	910	N/A	1	-	-	✓	-
eFlow6NX												-	-	-	✓
eFlow6N8	10.0-13.2	20.19-26.4	10.03-13.2	20.19-26.4	6A	3.5A	5A/250V	10A/32V	910	PD8UL	8	2.5A	-	✓	-
eFlow6NX8												2.5A	-	-	✓
eFlow6N8D	9.78-13.2	20.0-26.4	10.03-13.2	20.19-26.4	6A	3.5A	5A/250V	10A/32V	910	PD8ULCB	8	-	2A	✓	-
eFlow6NX8D												-	2A	-	✓
eFlow6N16	10.0-13.2	20.19-26.4	10.03-13.2	20.19-26.4	6A	3.5A	5A/250V	10A/32V	910	PD16W	16	2.5A	-	✓	-
eFlow6NX16												2 - PD8UL	2.5A	-	-
eFlow6N16D	9.78-13.2	20.0-26.4	10.03-13.2	20.19-26.4	6A	3.5A	5A/250V	10A/32V	910	PD16WCB	16	-	2A	✓	-
eFlow6NX16D												2 - PD8ULCB	-	2A	-



**eFlow6N Series  
Power Supply/Chargers**

**Specifications**

**Input**

Voltage 120VAC, 60Hz, 3.5A max.  
Fusing 5A / 250V.

**Outputs**

Voltage 12VDC or 24VDC selectable.  
Current 6A continuous max.  
Protection Fused 2.5A / PTC 2A.  
Auxiliary Class 2 power-limited @ 1A (unswitched).  
Other Overvoltage protection.  
Filtered and regulated.

**Back-up Battery (not included)**

Capacity 7AH / 12VDC (1 or 2 within enclosure).  
12AH / 12VDC (requires larger "X" enclosure).  
40AH, 65AH (requires separate enclosure).  
Type Sealed lead acid or gel type.  
Fuse Rating 10A @ 32VDC.  
Failover Upon AC loss, instantaneous.

**Fire Alarm Disconnect**

Supervised Latching or non latching.  
EOL 10K Resistor.

**Supervision**

AC Failure Form "C" contacts.  
Battery Form "C" contacts.

**Low DC Power Shutdown**

Shuts down DC output terminals if battery voltage drops below 71-73% for 12V units and 70-75% for 24V units (depending on the power supply). Prevents deep battery discharge.

**Indicators (LED)**

Input 120VAC is present.  
DC Output Powered.  
Battery Discharged or not connected.

**Agency Listings**

Access Control UL294.  
Burglar Alarm UL603, ULC-S318-96.  
Fire Alarm UL1481.  
California State Fire Marshall Approved.  
CE European Conformity.

**Physical and Environmental**

**Dimensions (H x W x D)**

eFlow6N, eFlow6N8(D), eFlow6N16(D):  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).  
eFlow6NX, eFlow6NX8(D), eFlow6NX16(D):  
15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm).

**Product Weight / Shipping (approx.)**

Model	Product Weight	Shipping Weight
eFlow6N	6.5 lbs. (2.95 kg)	7.4 lbs (3.3) kg
eFlow6NX	8.55 lbs. (3.88 kg)	9.65 lbs (4.38) kg
eFlow6N8(D)	6.65 lbs. (3.02 kg)	7.55 lbs (3.42) kg
eFlow6NX8(D)	8.5 lbs. (3.86 kg)	9.6 lbs (4.35) kg
eFlow6N16(D)	6.8 lbs. (3.08 kg)	7.7 lbs (3.49) kg
eFlow6NX16(D)	8.65 lbs. (3.92 kg)	9.75 lbs (4.42) kg

**Temperature**

Operating 0°C to 49°C (32°F to 120°F).  
Storage -20°C to 70°C (-4°F to 158°F).

**Relative Humidity  
BTU/Hr. (approx.):**

12VDC: 37 BTU/Hr.  
24VDC: 74 BTU/Hr.

**Accessories**

**Network Supervision**

Altronix model **LINQ2** Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Email and SNMP trap message notifications

