



DS-2CE56H1T-IT3

5 MP HD EXIR Outdoor Turret Camera

- 1/3" (5 MP) High-Performance CMOS
- HD Analog Output, up to 5 MP Resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens
- True Day / Night
- OSD Menu, DNR, Smart IR
- EXIR Technology, up to 131 ft (40 m) IR Distance
- IP67 Protection
- Up the Coax (HIKVISION-C)

Hikvision DS-2CE56H1T-IT3 EXIR Outdoor Turret Cameras are a versatile solution for all of your security needs. They feature a wide range viewing angle that captures images with a resolution of 5 MP at up to 20 fps. The Bullet Camera supports the Hikvision-Up-the-Coax protocol, and is equipped with an IR lamp with a range of up to 131 ft (40 m), which facilitates nighttime recording.



Available models: DS-2CE56H1T-IT3



DS-2CE56H1T-IT3 Image Sensor 1/3" (5 MP) Progressive Scan CMOS Effective Pixels 2592 (H) × 1944 (V) Minimum Illumination Color: 0.01 lux @ (F1.2,AGC ON), 0 lux with IR Shutter Time PAL: 1/25 s to 1/50,000 s NTSC: 1/30 s to 1/50,000 s Lens 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens Horizontal Field of View 86.5° (2.8 mm), 70.1° (3.6 mm), 46° (6 mm), 32.5° (8 mm), 20.9° (12 mm) Lens Mount M12 Day & Night ICR Angle Adjustment Pan: 0° to 340°; Tilt: 0° to 75°; Rotate: 0° to 355° Synchronization Internal synchronization Video Frame Rate 2592 x 1944 @ 20 fps HD Video Output 1 HD-TVI analog output AGC Supported D/N Mode Auto / color / BW (black and white) White Balance ATW / MWB **BLC** Supported Language English, Chinese Functions Brightness, sharpness, digital noise reduction, mirror, bad pixel correction, smart IR Operating Conditions -40° F to 140° F (-40° C to 60° C), Humidity 90% or less (non-condensing) Power Supply 12 VDC ± 30% Power Consumption Maximum 5 W IR Range Up to 40 m Communication Up-the-Coax Protocol: HIKVISION-C (HD-TVI output) Dimensions Φ 4.33" × 3.67" (Φ 110 mm × 93.2 mm) Weight 0.77 lbs (approximately 350g)


Accessories



CBS

Conduit Base

Dimensions



CMPL

Horizontal Pole Mount

