



PLCD SERIES MONITORS

PRODUCT FEATURES

- Active Matrix TFT
- High contrast ratio
- Space saving design
- 2x BNC composite inputs with loop through outputs
- S-Video in/out*
- VGA for PC input
- VESA compatible for versatile mounting
- Built-in speakers
- Gradual volume increase
- Remote control

ACCESSORIES

- PRMK08 – rack mount kit

Panasonic Security-Tough Monitors Offer Wide Range of Sizes and Inputs.

Equipped with a security-tough metal cabinet, the Panasonic lightweight, space-saving PLCD Series of video monitors offer a wide range of sizes (9" to 42") and inputs to handle whatever the video surveillance task. The PLCD Series feature an Active Matrix TFT LCD and LED displays with over 16 million colors to produce exceptional clarity and color detail. For easy mounting, all models are VESA compatible, and they include two built-in speakers with gradual volume increase for excellent audio. For easy wide screen viewing, the 16:9 PLCD42HDA, PLCD27HDA and PLCD24HDA boast high definition resolution and include a DVI and HDMI input.



PLCD9C



PLCD9C/2



PLCD15V



PLCD19P



PLCD27HDA



PLCD24HDA



PLCD42HDA

*Depends on model

SOLUTIONS FOR SECURITY

us.panasonic.com/security

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com

SPECIFICATION	PLCD9C*	PLCD9C/2*	PLCD15V*	PLCD19P	PLCD24HDA	PLCD27HDA	PLCD42HDA*
Screen Size	9.7"	9.7" x [2]	15"	19"	24"	27"	42"
Pixel Type	LCD/LED Active Matrix TFT	LCD/LED Active Matrix TFT	LCD Active Matrix TFT	LCD Active Matrix TFT	LED Active Matrix TFT	LED Active Matrix TFT	LED Active Matrix TFT
Contrast	500:1	500:1	600:1	800:1	5000:1	5000:1	3000:1
Max. Resoluton	1024 x 768	1024 x 768	1024 x 768	1280 x 1024	1920 x 1080	1920 x 1080	1920 x 1080
Brightness	300cd/m ²	300cd/m ²	250cd/m ²	250cd/m ²	250cd/m ²	300cd/m ²	350cd/m ²
Aspect Ratio	4:3	4:3	4:3	5:4	16:9	16:9	16:9
Viewing Angle (H/V)	140°/130°	140°/130°	160°/160°	160°/160°	178°/178°	178°/178°	178°/178°
Display Color	16.7 Million	16.7 Million	16.7 Million	16.7 Million	16.7 Million	16.7 Million	16.7 Million
Response Time	<35ms (typ.)	<35ms (typ.)	<8ms (typ.)	<5ms	<12ms (typ.)	<12ms	<6.5ms (gray to gray)
Speakers	1W x 2	1W x 2	2W x 2	2W x 2	2W x 2	2W x 2	2W x 2
Gradual Volume Increase	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Video In/Out (BNC)	2/2	2/2	2/2	2/2	2/2	2/2	2/2
S-Video In/Out	1/0	1/0	1/1	1/1	1/1	1/1	1/1
RGB In (15Pin D-Sub)	N/A	N/A	1	1	1	1	1
Component	N/A	N/A	N/A	1	1	1	1
DVI In /HDMI In	N/A	N/A	N/A	1/1	1/2	1/2	1/1
Audio In/Out (RCA)	1	1	1 set (L+R) / No Output	2/2	2/2	2/2	2/2
PC Stereo In/Out	1/0	1/0	1/0	1/1	1/1	1/1	1/1
Multi Display	N/A	N/A	N/A	PIP/PBP/VOV	PIP/PBP/VOV	PIP/PBP/VOV	PIP/PBP/VOV
Filter Type	3D Combfilter/ Deinterlace	3D Combfilter/ Deinterlace	RGB Vertical Stripe Color	3D Combfilter/ Deinterlace	3D Combfilter/ Deinterlace	3D Combfilter/ Deinterlace	3D Combfilter/ Deinterlace
Rackmount	N/A	Included	PRMK08	PRMK08	N/A	N/A	N/A
Vesa Mount Size	75mm x 75mm	75mm x 75mm	75mm x 75mm	100mm x 100mm	200mm x 200mm	200mm x 200mm	600mm x 100mm x 100mm
Outline Dimension (W x H x D)	8.46" x 7.44" x 2.81"	19" x 7.44" x 2.81"	13.82" x 13.7" x 7.87"	16.87" x 14.72" x 3.13"	22.87" x 15.6" x 7.09"	25.69" x 16.80" x 7.09"	38" x 22" x 26"
Gross Weight	6.2 lbs. (2.8kg)	15 lbs. (2.8kg)	12.57 lbs. (5.7kg)	15.8 lbs. (7.17 kg)	17.3 lbs. (8kg)	25.5 lbs. (12.5kg)	42 lbs (19kg)
Power Consumption	<20W	<20W	<36W	<42W	<43W	<48W	<67W
Electrical Ratings	AC100-240V (50/60Hz) DC 12V/1.5A	AC100-240V (50/60Hz) DC 12V/1.5A	AC100-240V (50/60Hz) DC 12V/3A	AC100-240V (50/60Hz) DC 12V/3.5A	AC100-240V (50/60Hz)	AC100-240V (50/60Hz)	AC100-240V (50/60Hz)
Regulations	TUV-NRTL(=UL), CB, DCC(A), CE-Emc(LVD)	TUV-NRTL(=UL), CB, DCC(A), CE-Emc(LVD)	UL, CB, FCC, CE	UL, CB, FCC(B), CE-Emc(LVD)	TUV-NRTL(=UL), CB, DCC(A), CE-Emc(LVD)	TUV-NRTL(=UL), CB, DCC(A), CE-Emc(LVD)	TUV-NRTL(=UL), CB, DCC(A), CE-Emc(LVD)

*OEM partnership

SOLUTIONS FOR SECURITY