

Monitor Wall

www.boschsecurity.com





- View multiple live cameras on large screens in your surveillance center
- ▶ Multi-channel decoder with single or dual-screen
- ► Configurable window layout
- ► Compatible with Bosch Video Management System and Bosch Video Client
- ▶ Compatible with all Bosch IP cameras and encoders

Monitor Wall is the easiest way to view many cameras on state-of-the-art monitor walls. They are the modern-day replacement for the familiar rows of analog CRT CCTV monitors and they bring very specific benefits. Because Monitor Wall is a digital software solution, it is not constrained by analog monitor dimensions. Instead it will easily drive the most massive to the tiniest displays, including flat panel plasma displays that are becoming so popular in both Network and Security Operations Centers. All the video is delivered by the high performance Bosch IP cameras and encoders, both MPEG-4 and H.264 and of course SD and HD.

Monitor Wall can be used in combination with Bosch VMS or Video Client to enhance display capabilities especially for large control centers. Used with VRM Server, which allows centralized management and control, an administrator is able to define user groups and associated privileges which is the basis for client access to live viewing, PTZ control, recording and retrieval, and eventual presentation on the Bosch Monitor Wall.

Together with the powerful video management software tools it is ideally suited for CCTV applications of any scale.

Depending on the performance of the PC and its graphic adapter, Monitor Wall can run a single or dual screen with different screen layouts, reaching from full screen to 5x5 or 6x5 view on both screens, depending on screen aspect ratio. The screen layout can be switched manually or automated by the management system or client if e.g. an alarm scenario requires a different view.



Monitor Wall is available as software only to be installed on any high-performance PC of your choice, but for added convenience there is also a choice of recommended hardware solutions.

Technical specifications

System Requirements

Hardware	Personal Computer
CPU	Intel Pentium Dual Core, 3.0 GHz or better
Hard Disk Interface	IDE or better
RAM	2 GB min
OS	Windows XP SP3 (32-bit)



Windows 7 (Business, Home; 32-bit, 64-bit in emulation mode) Graphics Card NVIDIA GeForce 8600 (PCI Express) NVIDIA Quadro FX 3500 PCIe NVIDIA Quadro FX 1500 PCIe NVIDIA Quadro FX 4500 PCIe NVIDIA Quadro FX 4600 PCIe NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall, Configuration Manager, MPEG-ActiveX)		
NVIDIA Quadro FX 3500 PCIe NVIDIA Quadro FX 1500 PCIe NVIDIA Quadro FX 4500 PCIe NVIDIA Quadro FX 4600 PCIe NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.)		
NVIDIA Quadro FX 1500 PCIe NVIDIA Quadro FX 4500 PCIe NVIDIA Quadro FX 4600 PCIe NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,	Graphics Card	NVIDIA GeForce 8600 (PCI Express)
NVIDIA Quadro FX 4500 PCIe NVIDIA Quadro FX 4600 PCIe NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro FX 3500 PCle
NVIDIA Quadro FX 4600 PCIe NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro FX 1500 PCle
NVIDIA Quadro FX 4800 PCIe NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro FX 4500 PCle
NVIDIA Quadro NVS 285 PCIe NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro FX 4600 PCle
NVIDIA Quadro NVS 440 PCIe ATI FireGL V7200 PCIe ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro FX 4800 PCle
ATI FireGL V7200 PCle ATI FireGL V3300 PCle Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro NVS 285 PCle
ATI FireGL V3300 PCIe Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		NVIDIA Quadro NVS 440 PCIe
Ethernet Card 100 Mbps Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		ATI FireGL V7200 PCle
Software DirectX 9.0c Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,		ATI FireGL V3300 PCle
Free Memory (Inst.) 100 MB (.NET environment, Monitor Wall,	Ethernet Card	100 Mbps
	Software	DirectX 9.0c
	Free Memory (Inst.)	· · · · · · · · · · · · · · · · · · ·

Software Features

Display	Single or Dual Screen (span mode)
	Configurable windows
	Simultaneous viewing of multiple video streams. (Performance will vary according to the video compression settings of each stream and the nature of the scene.)
Configuration	Through Configuration Manager 4.22.0030 or newer
	Automatically through video management system

Ordering information

MVS-MW Monitor Wall License

Digital software solution to view many cameras on state-of-the-art monitor screens (e-license) Order number MVS-MW

Represented by:

Americas:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180 security.sales@us.bosch.com www.boschsecurity.us

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 latam.boschsecurity@bosch.com www.boschsecurity.com

© Bosch Security Systems 2013 | Data subject to change without notice 1543965451 | en, V3, 04. Oct 2013