

AL400ULX Series Power Supply/Chargers

Description

Altronix AL400ULX series power supply/chargers convert a 115VAC, 60Hz input into a single fused, four (4), eight (8) or sixteen (16) fuse or PTC protected outputs. Outputs are selectable for 12VDC with a total of 4A max. or 24VDC with a total of 3A max.



AL400ULPD8

Key Features

- Available with 1, 4, 8 or 16 outputs.
- Fused or PTC protected outputs.
- Supervision:
 - AC Fail
 - Battery Fail and Battery Presence.
- Built-in charger for sealed lead acid or gel type batteries.
- Instantaneous transfer to stand-by batteries.
- Short circuit and overload protection.
- AC input and DC output options.
- UL Listed in the U.S. and Canada.
- CSFM and MEA Approved.
- Lifetime Warranty / Made in the U.S.A.
- All units are available in grey or red enclosure*.

*AL400ULXJ's enclosure is red. For grey enclosure order model AL400ULXJG

AL400ULX Series Power Supply Configuration Reference Chart

Altronix Model Number	12VDC Total Output Rating (A)	24VDC Total Output Rating (A)	Input Rating: 115VAC, 60Hz	Input Fuse Rating	Power Supply Output Fuse Rating	Power Distribution Module	Number of Outputs	Fused Output Ratings	PTC Auto-Resettable Outputs Ratings	Accommodates Batteries
AL400ULX	4A	3A	3.5A	5A/250V	15A/32V	N/A	1	3.5A	—	Two (2) 7AH
AL400ULXX						N/A	1	3.5A	—	Two (2) 12AH
AL400ULXJ(G)						N/A	1	3.5A	—	Two (2) 18AH
AL400ULPD4						PD4UL	4	3.5A	—	Two (2) 7AH
AL400ULPD4CB						PD4ULCB	4	—	2.5A	Two (2) 7AH
AL400ULPD8						PD8UL	8	3.5A	—	Two (2) 7AH
AL400ULPD8CB						PD8ULCB	8	—	2.5A	Two (2) 7AH
AL400ULXPD16						Two (2) PD8UL	16	3.5A	—	Two (2) 12AH
AL400ULXPD16CB						Two (2) PD8ULCB	16	—	2.5A	Two (2) 12AH

AL400ULX Series

Power Supply/Chargers



Specifications

Input

Voltage 115VAC, 60Hz, 3.5A max.
Fusing 5A / 250V.

Outputs

Voltage 12VDC or 24VDC selectable.
Current 4A @ 12VDC or 3A @ 24VDC continuous max.
Protection Fused 3.5A / PTC 2.5A.
Other Overvoltage protection.
Filtered and regulated.

Back-up Battery *(not included)*

Capacity 7AH / 12VDC (1 or 2 within enclosure).
12AH / 12VDC (requires larger "X" enclosure).
18AH / 12VDC (requires larger "J" enclosure).
40 AH / 65 AH (requires separate enclosure).
Type Sealed lead acid or gel type.
Fuse Rating 15A @ 32VDC.
Failover Upon AC loss, instantaneous.

Supervision

AC Failure Form "C" contacts.
Battery Form "C" contacts.

Indicators (LED)

Input 120VAC is present.
DC Output Powered.
Battery Discharged or not connected.

Agency Listings

Access Control UL294
Burglar Alarm UL603
Hospital Signaling UL1069
Fire Alarm UL1481
California State Fire Marshall Approved

Physical and Environmental

Dimensions (H x W x D)

AL400ULX, AL400ULPD4(CB), AL400ULPD8(CB):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).

AL400ULXX, AL400ULXPD16(CB):
15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm).

AL400ULXJ:
18" x 14.5" x 4.625" (457.2mm x 368.3mm x 117.48mm).

Product / Shipping Weight (approx.)

Model	Product Weight	Shipping Weight
AL400ULX	8.65 lbs. (3.86 kg)	9.55 lbs. (4.26 kg)
AL400ULXX	10.1 lbs. (4.58 kg)	11.4 lbs. (5.17 kg)
AL400ULXJ(G)	11.5 lbs. (5.22 kg)	13.7 lbs (6.21 kg)
AL400ULPD4(CB)	8.45 lbs. (3.83 kg)	9.35 lbs (4.24 kg)
AL400ULPD8(CB)	8.7 lbs. (3.95 kg)	9.6 lbs (4.35 kg)
AL400ULXPD16(CB)	10.1 lbs. (4.58 kg)	11.4 lbs (5.17 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr (approx.):

12VDC: 25 BTU/Hr.
24VDC: 37 BTU/Hr.