

AXIS T8344 Power On/Off Plug

Wireless power on/off plug

AXIS T8344 Power On/Off Plug enables remote on/off switching of lamps and other devices. By communicating wirelessly with AXIS M5065 PTZ Network Camera or connected Z-Wave Plus® controllers, the power on/off plug can be used in small security solutions with less cabling. Designed to act as a repeater, AXIS T8344 can increase the wireless range of the security solution by up to 100 m. It has two supported outlets: one controllable and one pass-through. The wireless I/O connectivity also enables flexible installation as the relay can easily be moved and adapted to your needs.

- > **Wireless I/O connectivity**
- > **Z-Wave Plus® compatibility**
- > **S2 security compliant**



AXIS T8344 Power On/Off Plug

| | | | |
|-----------------------------|--|--|--|
| Supported products | AXIS M5065 PTZ Network Camera Compatible with other Z-Wave Plus® control devices | Storage conditions | -20 °C to 60 °C (-4 °F to 140 °F) |
| Network | | Approvals | EMC FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B Safety UL 244A |
| Supported protocols | Z-Wave Plus®. For more information on the supported command classes, see the product's User Manual | Dimensions | 68 x 56.3 x 110 mm (2.68 x 2.22 x 4.33 in) |
| General | | Weight | 152 g (0.33 lbs) |
| Casing | Plastic Color: white | Included accessories | Installation guide |
| Sustainability | PVC free | Warranty | Axis 3-year warranty, see www.axis.com/warranty |
| Power | AC 100-120 V, 50-60 Hz, max load 1400 W (US), 1200 W (JP) | Environmental responsibility: www.axis.com/environmental-responsibility | |
| Distance | Transmitting range up to 100 meters (328 ft) | | |
| Frequency | 908.42 MHz (US), 922.5 MHz (JP) | | |
| Operating conditions | -10 °C to 40 °C (14 °F to 104 °F) | | |