

DS-2CD6626BS-R

2 MP Ultra Low-Light and WDR Anti-Corrosion Bullet Camera



- 1/1.8" Progressive Scan CMOS Sensor
- Darkfighter Ultra-Low Illumination Technology
- 1920 x 1080 @ 60 fps
- 316 L Stainless Steel Housing
- WF2, C5-M Anti-Corrosion Standard
- 120 dB WDR
- Full Smart Feature-set
- NEMA 4x Certification
- IP67 Certified




Hikvision DS-2CD6626BS-R Network Bullet Cameras are a smart choice for difficult environmental conditions. They are equipped with a 1920 x 1080 lens that records HD images at 60 fps. It also features a IP67 316 L stainless steel housing that exceeds WF2 and C5-M anti-corrosion standards and protects your camera from outside elements that are otherwise detrimental to microelectronics.

The camera also contains the standard set of Hikvision proprietary Smart Features that power analytics such as scene change and intrusion detection.

Available models:
DS-2CD6626BS-R

DS-2CD6626BS-R	
Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Minimum Illumination	Color: 0.002 Lux @ (F1.2, AGC ON); B/W: 0.0002 Lux @ (F1.2, AGC ON)
Shutter Speed	1 s to 1/100,000 s
Slow Shutter	Supported
Lens	16 mm F1.8 HFOV: 25°
Lens Mount	M12
Day and Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	120 dB
Compression Standard	
Video Compression	H.264 / MJPEG / MPEG4
H.264 Encoding Level	Baseline profile/ main profile/ high profile
Video Bit Rate	32 Kbps to 16 Mbps
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2
Audio Bit Rate	64 Kbps (G.711) / 16 Kbps (G.722.1) / 16 Kbps (G.726) / 32 to 128 Kbps (MP2L2)
Image	
Maximum Resolution	1920 × 1080
Frame Rate	50 Hz: 50 fps (1920 × 1080, 1280 × 960, 1280 × 720); 60 Hz: 60 fps (1920 × 1080, 1280 × 960, 1280 × 720)
Third Stream	Independent with Main Stream and Sub Stream, up to: 50 Hz: 25 fps(1920 × 1080);60 Hz: 30 fps (1920 × 1080)
Image Settings	Rotate mode, saturation, brightness, contrast and sharpness are adjustable by client software or web browser
Backlist Compensation	Yes, zone optional
Defog	Supported
EIS	Supported
HLC	Supported
Day / Night Switch	Auto, schedule, alarm trigger
Picture Overlay	Support for 24-bit BMP image overlay, zone optional
ROI	Up to 4 fixed areas in each stream or dynamic tracking
Network	
Network Storage	NAS (support for NFS, SMB / CIFS)
Alarm Trigger	Tampering alarm, Network disconnect, IP address conflict, Storage full, storage error
Smart Features	Line crossing detection, scene change detection, intrusion detection, audio exception detection, defocus detection, motion detection, face detection, region entrance/ exiting detection, loitering detection, rapid motion detection , unattended baggage / object removal detection, parking detection, dynamic analysis, object counting, vehicle detection etc.
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF(PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General Functions	One-key recovery, flash-prevention, three streams, heartbeat, mirror, password protection, video cover, watermark, IP address filtering, anonymous access
Interface	
Audio Interface	1-ch 3.5 mm audio in (microphone in / line in) / output external interface
Communication	1 10M/100M Ethernet port , 1 RS-485 port, 1 RS-232 interface Housing
Housing Interface	1 anti-corrosion inlet protected by a metal hose
Alarm	1 input / 1 output, up to 110 VAC (1 A) or 24 VDC (500 mA)
General	
Operating Conditions	-22° F to 140° F (-30° C to 60° C); Humidity 95% or less (non-condensing)
Power Supply	24 VAC / 12 VDC / PoE (802.3at)
Power Consumption	13 W maximum
Dimensions	14.69" x 8.00" x 7.08" (373.03 mm × 203.15 mm × 180 mm)
Weight	13.67 lbs (6.2 kg)

Accessories

<p>JBM-SS</p>	 <p>WB-SS</p>
---------------	----------------------------------------------------------------------------------------------------

