



ALT V244300CB

Overview

ALT V244300CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Four (4) PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current (3.13 amp per device, 2.5 amp max.) or 28VAC @ 10 amp (300VA) supply current (2.5 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 153.55 BTU/Hr.
 - 28VAC: 143.31 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm)
- Product weight (approx.): 11.1 lbs. (5.1 kg).
- Shipping weight (approx.): 11.7 lbs. (5.3 kg).

Agency Approvals



European Conformity

