

960H IR Indoor/Outdoor Turret Camera

- VLEDT1HG** 2.8-12mm auto iris varifocal lens, dark grey housing
- VLEDT1HW** 2.8-12mm auto iris varifocal lens, white housing
- VLEDT2HG** 3.6mm fixed lens, dark grey housing
- VLEDT2HW** 3.6mm fixed lens, white housing

Features

- 1/3" 960H CCD
- 0 lux with 36 IR LEDs built-in (VLEDT1HG/VLEDT1HW)
- 0 lux with 24 IR LEDs built-in (VLEDT2HG/VLEDT2HW)
- 98' IR range (depending on scene reflection) (VLEDT1HG/VLEDT1HW)
- 65' IR range (depending on scene reflection) (VLEDT2HG/VLEDT2HW)
- IP66 compliant
- 2 year warranty



Specifications

Image Sensor	1/3" 960H CCD	Gamma	0.45 typ.
Resolution	700 TV lines	Scanning System	2:1 interlace
Minimum Illumination	0.01 lux, 0 lux with IR on	Synchronization	Internal
Effective Pixels	976 (H) x 494 (V)	Video Signal Output	1.0Vp-p / 75 ohms
Number of IR LEDs	VLEDT1HG/VLEDT1HW: 36	Operating Temperature	14° F – 122° F
	VLEDT2HG/VLEDT2HW: 24	Storage Temperature	-4° F – 140° F
IR Range	VLEDT1HG/VLEDT1HW:	Power Consumption	Max. 80mA (IR off)
	Up to 98' (depending on scene reflection)		VLEDT1HG/VLEDT1HW: max. 400mA (IR on)
	VLEDT2HG/VLEDT2HW:		VLEDT2HG/VLEDT2HW: max. 300mA (IR on)
	Up to 65' (depending on scene reflection)	Power Supply	12VDC (power supply not included)
IR LED Wavelength	850nm	Dimensions	VLEDT1HG/VLEDT1HW: 4.25" (H) x 4.5" (Dia.)
IR Status	IR on: under 10 lux, by CDS auto control		VLEDT2HG/VLEDT2HW: 3.2" (H) x 3.6" (Dia.)
Electronic Shutter	Auto (1/60 sec. - 1/100,000 sec.)	Weight	VLEDT1HG/VLEDT1HW: 1.2 lbs.
S/N Ratio	More than 52dB		VLEDT2HG/VLEDT2HW: 10.4 oz.
Backlight Compensation	Auto		
White Balance	Auto		
AGC	Auto		

Optional Accessory



PSW5
12VDC
Power Supply

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/25/14