A1 SECURITY CAMERAS
The First Name in Security

speco technologies®

WiFi Adapter for IP Cameras

WIFIMOD

IP WiFi

Features

- Converts Speco IP cameras to WiFi
- Dual-band WiFi (2T2R 802.11n)
- Easy setup through mobile app – no need to log into the camera through a web viewer to connect it to an access point
- PoE for providing power to the camera
- Works with Speco Connect
- 2 year warranty

Wireless Specifications

WiFi 2T2R, 802.11b/g/n
Frequency 2.4GHz
Data Rate ..... Up to 300Mbps
Security ..... WEP (40-bit, 128-bit) WPA/WPA2 (TKIP, AES)
Antenna ..... SMA type dipole

External Terminal Specifications

Ethernet ..... 10/100 Mbps
Power ..... DC jack

Network Specifications

Protocols ..... IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS

Client Specifications

Setup ..... Speco Connect (iPhone® and Android™)

Operating & Unit Specifications

Power 48VDC
Operating Temperature... 32°F -113°F
Operating Humidity ..... 8% - 80% RH
Unit Dimensions ..... 1.8”(W) x 0.8”(H) x 3.3”(L)
Unit Weight ..... 1 lb.
Certifications ..... FCC, RoHS

Optional Accessories

APRPT
WiFi AP & Repeater

*Visit www.specotech.com/onvif.html for latest ONVIF® support. ONVIF is a trademark of Onvif, Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/23/16

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com