



Microphone Mixers

Speco Technologies' line of microphone mixers offers performance, style and quality at an affordable price. These mixers are ideal for schools, houses of worship, clubs, board rooms, musicians, etc. For commercial audio purposes, use one of our MMB series mixers to expand the number of microphones you can plug into an amplifier.

MMB3XLR 3 Channel Microphone Mixer

Features

- · 3 XLR inputs with separate volume controls for mixing
- · Headphone/Aux output
- · One balanced XLR output
- · Operates off 12V power supply (included) or two 9V batteries (not included)



Specifications

THD≤0.05% Max. Output Level14dB Max. Input Level-14dB Max. Gain60dB Low Cut-3dB@100Hz Max. S/N Ratio74dB

Phantom Power.......18VDC (via two 9V batteries - not included)

Input Impedance......600 Ohms Output Impedance 600 Ohms

Dimensions......5.63" (W) x 1.77" (H) x 3.66" (D)

MMB8XLRLL 8 Channel XLR & Line Level Mixer

Features

- 1U rack-mountable with attached brackets
- · 8 channels of total inputs
 - 6 channels of XLR & ¼" inputs
 - 2 channels of RCA & ¼" inputs
- Single 1/4" unbalanced & XLR balanced output
- · RCA pre-fade out
- · Tone controls
- · Internal jumper for direct channel output



Specifications

THD≤0.05% Max. Output Level14dB Max. Input Level-14dB Max. Gain60dB Low Cut-3dB@100Hz Max. S/N Ratio74dB Phantom Power.......18VDC (via two 9V batteries - not included) Input Impedance......600 Ohms Output Impedance 600 Ohms Dimensions......5.63" (W) x 1.77" (H) x 3.66" (D)

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/31/12