4MP Network IR Fixed Dome Camera

IPC3614SR3-DPF28 (36)(60)

Key Features

Optics

- Day/night functionality
- Up to 120 dB WDR (Wide Dynamic Range)
- SmartIR, up to 30 m (98 ft) IR distance

Compression

- Ultra 265, H.264, MJPEG
- Embedded smart algorithm
- Triple streams
- 9:16 corridor format

Network

- ONVIF Conformance

Structure

- Wide temperature range: -35°C to 60°C (-31°F to 140°F)
- Wide voltage range of ±25%
- 4 KV surge protection designed for network interface
- IP67
- 3-Axis

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com

Specifications

	IPC3614SR3-DPF28	IPC3614SR3-DPF36	IPC3614SR3-DPF60
Camera			
Sensor	1/3", progressive scan,4.0 megapixel, CMOS		
Lens	2.8mm@F2.0	3.6mm@F2.0	6mm@F2.0
DORI Distance	Lens / Detect(m) / Observe(m) / Recognize(m) / Identify(m)		
	2.8mm / 63 / 25.2 / 12.6 / 6.3		
	3.6mm / 81 / 32.4 / 16.2 / 8.1		
	6mm / 135 / 54 / 27 / 13.5		
Angle of view(H)	104.4°	76.5°	49.9°
Angle of View (V)	67°	53.2°	32.9°
Angle of View (O)	135.7°	99.5°	61.4°
Adjustmentangle	Pan: 0°~360°	Tilt: 0°~90°	Rotate:0°~360°
Shutter	Auto/Manual, 1~1/100000 s		
Minimum Illumination	Colour: 0.03 Lux (F2.0, AGC ON) 0 Lux with IR		
Day/Night	IR-cut filter with auto switch (ICR)		
Digital noise reduction	2D/3D DNR		
S/N	>52 dB		
IR Range	Up to 30m (98 ft) IR range		
Defog	Digital Defog		
WDR	120dB		
AWB(Auto white balance)	Auto/manual		
Gain Control	Auto/manual		
Video			
Video Compression	Ultra 265, H.264, MJPEG		
Frame Rate	Main Stream:4MP (2592×1520): Max. 20 fps，4MP (2560×1440): Max. 25 fps，3MP (2048×1520): Max. 30 fps; Sub Stream:2MP (1920×1080): Max. 30 fps; Third Stream:D1(720×576) : Max. 30fps		
HLC	Supported		
BLC	Supported		
9:16 Corridor Mode	Supported		
OSD	Up to 8 OSDs		
Privacy Mask	Up to 8 areas		
ROI	Up to 8 areas		
Motion Detection	Up to 4 areas		
Smart			
Behavior Detection	Intrusion, cross line, motion detection		
Intrusion	Enter and loiter in a pre-defined virtual region		
cross line	Cross a pre-defined virtual line		
motion detection	Moving within a pre-defined virtual region		
Recognition	Face detection、Audio detection		

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com

Intelligent Identification	Defocus, Scene Change, Object Left, Object Moving
Statistical Analysis	People counting
General Function	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible Integration	ONVIF(Profile S), API
Interface	
Network	1 RJ45 10M/100M Base-TX Ethernet
General	
Power	12 V DC±25%, PoE (IEEE802.3 af)
	Power consumption: Max 5W
Dimensions (Ø x H)	Φ126 x 94 mm (Ø5.0" x 3.7")
Weight	0.33 kg (0.73lb)
Operating Conditions	-35°C ~ +60°C (-31°F ~ 140°F), Humidity:10%~ 95% RH(non-condensing)
Ingress Protection	IP67

Dimensions



Zhejiang Uniview Technologies Co.,Ltd.
South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R.China 310051
Email：overseasbusiness@uniview.com;globalsupport@uniview.com
http://www.uniview.com
©2016-2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.
*Product specifications and availability are subject to change without notice.

Available from A1 Security Cameras
www.a1securitycameras.com email: sales@a1securitycameras.com