




Platinum HD-TVI Turret Camera 2MP CMHT2722B-28




Key Features:

- 2MP High Definition
- 1920x1080P@30fps
- 2.8mm Fixed Lens
- 1 Matrix IR up to 131ft(40m)
- DC 12V
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

Dimensions:





















©2018 LT Security, Inc. | info@LTSecurityinc.com | www.LTSecurityinc.com







Platinum HD-TVI Turret Camera 2MP CMHT2722B-28

CAMERA	
Image Sensor	1/2.9" CMOS
Signal System	NTSC/PAL
Effective Pixels	1930(H)*1088(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Shutter Speed	1/30(1/25) s to 1/50,000 s
Lens	2.8mm
	Angle of View: 105.8°
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1080p@30fps/1080p@25fps
HD Video Output	1 HD-TVI Output
S/N Ratio	More than 52dB
MENU	
AGC	Support
D/N Mode	Color/ BW/ Smart
White Balance	ATW/MWB
Language	English
Function	Digital noise reduction, Mirror
GENERAL	
Working Temperature	-40 ° F - 140 ° F (-40 ° C - 60 ° C)
/Humidity	Humidity 90% or less (non-condensing)
Power Supply	DC 12V
Power Consumption	Max. 3.5W
Weather Proof Ratings	IP66
IR Range	Up to 131ft(40m)
	Up to 131ft(40m) φ 5.0" \times 4.0"(φ 126.7 \times 102.1mm)