

Features

- 3 MP 1/3" CMOS Sensor
- 4mm Fixed Lens
- 3D DNR
- 1080P@30fps
- 30 IR LED@90ft
- POE; DC 12V
- IP66

Specifications

Model	CMIP3432	
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.05 lux @F1.2, AGC ON, 0 lux with IR 0.14 lux @F2.0, AGC ON, 0 lux with IR
	Shutter time	1/25s ~ 1/100,000s
	Lens	4mm @F2.0 Angle of view: 45.3°
	Lens Mount	M12
	Day& Night	IR cut filter with auto switch
Compression Standard	Digital noise reduction	3D DNR
	Video Compression	H.264 / MPEG4 / MJPEG
Image	Bit Rate	32 Kbps ~ 16 Mbps
	Max. Image Resolution	2048 x 1536
	Frame Rate	15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
	Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
	BLC	Yes, zone configurable
Network	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Security	User authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
	Mobile App	Guardian Expert for iPhone/iPad,/Android
Interface	Communication Interface	1 RJ45 10M / 100M ethernet interface
General	Operating Conditions	-25 °C ~ 60 °C (-13°F ~ 140 °F) humidity 95% or less (non-condensing)
	Power Supply	12 VDC ± 10%, PoE (802.3af)
	Power Consumption	max. 5.5W
	Weather Proof	IP66
	IR Range	Up to 90ft
	Dimensions	Φ111 × 82 (4.4" × 3.2")
	Weight	1.1 lb(500g)


IP66

Dimensions

