

WRT-3301

Dual-purpose Wisenet WAVE Network Video Recorder



The WRT-3301 is a dual purpose Wisenet WAVE server and client built into a compact mini-tower form factor. This ready to deploy solution can manage up to 170 Mbps of recording throughput on up to 32TB of storage for a single site, or as an addition to your existing Wisenet WAVE system.

Key Features

- Preloaded and configured with Wisenet WAVE video management system
- Includes (4) four Wisenet WAVE Professional licenses
- 170 Mbps of recording throughput
- Up to 32TB Internal Storage
- Dual Gigabit Ethernet
- Includes USB mouse and keyboard
- Includes front panel with lock
- Supports Wisenet and ONVIF conformant IP cameras



| WRT-3301 |
|---|
| |
| Wisenet WAVE |
| 4x Wisenet WAVE Professional license |
| 170 Mbps |
| 1 x 64GB SSD (internally mounted) |
| 4 x 3.5" (front accessible) |
| Up to 32TB raw |
| N/A |
| 2 x RJ-45, Gigabit Ethernet |
| Intel Core i3-7101E, 3.9GHz |
| 4GB DDR4 |
| Windows 10 IoT Enterprise |
| 2x HDMI, 1x DVI |
| 4x USB 3.0 (rear), 1x USB 3.0 Type-C (rear), 2x USB 2.0 (front) |
| IEEE 802.11ac |
| 1x PS2, 2x Wi-Fi antennas, 3.5mm audio in/out, 1x SPDIF out |
| Included |
| |

| MECHANICAL / ELECTRICAL / ENVIRONMENTAL |
|---|
|---|

| Color / Material | Black, Silver / Metal |
|---------------------|--|
| Dimensions | 7.87" x 10.63" x 12.2" (200mm x 270mm x 310mm) |
| Weight | 15.4lbs (7kg) |
| Power Supply | 250W |
| Power Input | 100 ~ 240V AC |
| Operating | 32°F to 122°F (0°C to 50°C) |
| Storage Temperature | -4°F to 176°F (-20°C to 80°C) |
| Operating Humidity | 5% to 85% RH |
| | UL, cUL, CB, FCC |
| | Dimensions Weight Power Supply Power Input Operating Storage Temperature |

* Weight is on chassis without HDDs *The latest product information / specification can be found at www.hanwhasecurity.com * Bandwidth performance figures based on performance testing by Hanwha Techwin using Wisenet WAVE

Dimensions Unit: inch (mm)



