



VLB2A

2.8mm fixed lens, white housing







Features

- Supports HD-TVI, AHD, HD-CVI and analog outputs 1
- Supports Full HD 1080p @ 30fps
- Adaptive IR LEDs reduce IR saturation
- Full OSD operation through UTC control (up the coax)
- IR Range: 98' (depending on scene reflection)
- IP67 compliant, weather resistant
- Junction box included
- UL listed
- 5 year warranty



Included
Junction Box
(O2VLJBBW)



Camera Specifications	
Image Sensor	1/2.9" CMOS, 2MP
Minimum Illumination	0.02 lux
Supported Resolution	1920 x 1080
Scanning System	Progressive
IR LEDs	18
IR Distance	98 ft. (depending on scene reflection)
White Balance	Auto / Manual
Compensation	WDR (BLC / HLC)
Day / Night	Auto / Manual
DNR	2D

Operating & Unit Specifications	
Power	12VDC (power supply not included)
Power Consumption	2.8W max.
Operating Temperature	-22°F - 140°F
Operating Humidity	0% - 95% RH
Unit Dimensions	2.8" (Dia.) x 6.5" (L)
Unit Weight	1 lbs.
Certifications	FCC, UL, RoHS

Optional Accessories



O3PMT Bullet Pole Mount (use with junction box)



PSW5 12VDC Power Supply

¹Camera is defaulted to HD-TVI. ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/23/18