

Series 25 In-Ceiling Speaker Line

SP525C

5.25" in-ceiling speaker

SP625C

6.5" in-ceiling speaker

Features

- Stylish baffle design
- Pivoting tweeter



sold in pairs

Specifications

Specifications	SP625C	SP625C
RMS Power	30W	40W
Max. Power.....	60W	80W
Termination Type	Press Terminal	Press Terminal
Sensitivity (1W/1M).....	87dB	89dB
Maximum SPL (Pmax/1M).....	94.3dB	95.5dB
Driver Impedance	8 Ohms	8 Ohms
Magnet.....	10 oz. ferrite	11.6 oz. ferrite
Frequency Response Range...	70Hz ~ 20Hz	50Hz ~ 20Hz
Dispersion @ 1000Hz	85° conical	85° conical
Driver	5.25" Polypropylene woofer 0.75" Silk tweeter	6.5" Polypropylene woofer 1" Silk tweeter
Speaker Dimensions	8" (Dia.) x 4" (D)	9.25" (Dia.) x 4.25" (D)
Mounting Dimensions	6.6" (Dia.)	7.75" (Dia.)
Minimum Mounting Depth.....	3.5"	3.75"
Weight	2.4 lbs.	3 lbs.
Material.....	Baffle: ABS Grille: Metal	Baffle: ABS Grille: Metal
Color	White	White

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 8/28/14

Optional Accessories



BRC5
Mounting Bracket
(use with SP525C)



BRC6
Mounting Bracket
(use with SP625C)