

SP6CSL 2 x 3", white housing, 8 Ohms**Features**

- Mounting depth of 2" means this speaker can fit into the tightest of ceilings
- 5 total speakers (2 Woofers, 2 Midrange and 1 Tweeter) helps maintain great sound even with the limited space
- Magnetic Grille helps ensure an easy installation

Speaker Specifications

RMS Output Power	30W
Max Output Power	60W
Sensitivity (1W/1M)	90dB
Maximum SPL (Pmax/1M)	106dB
Impedance	Woofer: 16 Ohms Midrange: 16 Ohms Tweeter: 8 Ohms
Magnet Material and Weight	Ferrite, 3 oz woofer, 2.6 oz midrange
Frequency Response Range	125Hz - 20kHz
Dispersion	150°
Driver	3" coated paper cone, rubber edge woofer 3" coated paper cone, rubber midrange .75 silk dome tweeter

Operating Specifications

Dimensions	11" (D) x 2.3" (H)
Mounting Depth	2"
Cutout Dimensions	9.6"
Speaker Weight	4.4 lbs
Speaker Body Material	ABS
Speaker Grille Material	Steel



Includes Grille



Side View

Optional Accessories

BRC8F
Ceiling Tile
Mount Bracket



T7020
20W 70V
Line Transformer



T7010
10W 70V
Line Transformer



T70255
5W 70/25V
Dual Transformer