

Portable CCTV Installation & Testing Monitor

VMS2

Features

- LCD display easily allows for checking the video signal of the CCTV camera being tested
- An audio jack tests the audio signal
- Built-in rechargeable battery has a life of 4 hours
- An LED light displays low battery level
- Visor blocks out sunglare on the LCD display
- The heavy duty casing, durable handle and shoulder belt (included) make this unit conveniently portable
- 1 year warranty



Specifications

Resolution.....	480 x 234
Brightness	350cd
Input Video Signal	1.0Vp-p (sync., negative) termination 75 Ohm
LCD Technology	TFT active matrix
Display Size	4"
Contrast Ration.....	250:1
View Angle.....	L/R $\pm 45^\circ$ U/D: $10^\circ/30^\circ$
Audio Input	30 mVp-p – 100 mVp-p
Audio Output.....	0.5W max
Charging Time	8 hours charging time, 4 hours operating time
Video/Audio Connector.....	RCA W/BNC plug adapter
Power Consumption	4.5W
Rechargeable Battery	12V.1.1AH
Power Supply	12VDC (power supply included)
Dimensions	6" (W) x 5.1" (H) x 3" (D)
Weight	4.3 lbs.
Extra battery available.....	BVMS2



Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation.
Spec Rev. 10/7/11