

AXIS M1113-E Network Camera

Outdoor-ready, compact and adaptable SVGA camera

AXIS M1113-E with CS-mounted, varifocal DC-iris lens provides excellent image quality without motion blur in SVGA resolution, where progressive scan provides crisp and clear images even in low-light areas. It offers multiple H.264 and Motion JPEG streams that can be individually optimized for bandwidth and storage efficiency. The pixel counter helps verifying that the pixel resolution of an object or face fulfills regulatory or specific customer requirements. Installation outdoors is easy thanks to Power over Ethernet support, a removable sunshield and a wall bracket. The casing is made of UV resistant polymer and the operating temperature ranges from -20 °C to 50 °C (-4 °F to 122 °F).

- > **SVGA quality**
- > **Outdoor-ready, IP66 rating**
- > **Varifocal DC-iris lens**
- > **Power over Ethernet**
- > **Pixel counter**



AXIS M1113-E Network Camera

Camera		Email Notification via email, HTTP and TCP Pre- and post-alarm video buffering External output activation, Video recording to edge storage, Go to PTZ preset, Guard tour	
Image sensor	Progressive scan RGB CMOS 1/4"		
Lens	Varifocal, 2.9-8.2 mm, F1.4 Horizontal angle of view: 65°-25°		
Minimum illumination	0.6 lux, F1.4		
Shutter time	1/8000 s to 1/6 s		
Video		Data streaming	
Video compression	H.264 Baseline Profile (MPEG-4 Part 10/AVC), Motion JPEG	Event data	
Resolutions	800x600 to 160x90	Built-in installation aids	
Frame rate	30 fps in all resolutions	Pixel counter	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Controllable frame rate and bandwidth, VBR/CBR H.264	General	
Pan/Tilt/Zoom	Digital PTZ	Casing	Color: White NCS S 1002-B IP66-rated acrylate enclosure
Image settings	Compression, Color, Brightness, Sharpness, Contrast, White balance, Backlight compensation, Mirroring of images, Rotation - including Corridor Format, Text and image overlay, Privacy mask Rotation: 0°, 90°, 180°, 270°	Memory	128 MB RAM, 128 MB Flash
Network		Power	Power over Ethernet IEEE 802.3af Class 1
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, Digest authentication, User access log	Connectors	RJ45 10BASE-T/100BASE-TX PoE
Supported protocols	IPv4/v6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	Edge storage	Support for recording to dedicated network-attached storage (NAS) For NAS recommendations see www.axis.com
System integration		Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 15-100% RH (condensing)
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform, specifications at www.axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S, specification at www.onvif.org	Approvals	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1
Analytics	Video motion detection, Active tampering alarm Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line Detection, AXIS Digital Autotracking and third-party applications, see www.axis.com/acap	Weight	780 g (1.72 lb)
Event triggers	Analytics, Edge storage events, External input, Time scheduled	Included accessories	Installation Guide, Windows decoder 1-user license Wall bracket, Sunshield, Desiccant bag
Event actions	File upload via FTP, HTTP and network share	Optional accessories	Axis Mounts, Axis Housings & Cabinet, Axis Midspans, Axis Illuminators, Lenses For more accessories, see www.axis.com
		Video management software	AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on www.axis.com/techsup/software
		Languages	German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese
		Warranty	Axis 1-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).

More information is available at www.axis.com

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).

More information is available at www.axis.com