

R615DC1016 Series

DC CCTV Rack Power Supplies

Altronix R615DC1016 Series Rack Mount CCTV Power Supplies provide 6-15VDC distributed via sixteen (16) fuse or PTC protected outputs for powering CCTV cameras, heaters, and other video accessories.



R615DC1016CB

Key Features

- Sixteen (16) fuse or PTC protected outputs
- 6-15VDC output voltage
- Filtered and electronically regulated outputs
- Short circuit and thermal overload protection
- Illuminated master power disconnect circuit breaker with manual reset
- Sixteen (16) power LEDs
- 3-wire grounded line cord
- Removable terminal blocks with locking screw flange
- Spare fuses provided
- CE European Conformity
- Lifetime Warranty

R615DC1016 Series Power Supply Configuration Reference Chart

Altronix Model Number	115VAC 50/60Hz Input Current	Total Output Current	Output Voltage	Number of Outputs	PTC Protected Outputs (auto-resettable)	Fuse Protected Outputs	Output Current (max per output)
R615DC1016	1.9A	10A	6-15VDC	16	—	✓	3.5A
R615DC1016CB					✓	—	2.5A

Specifications

Input

Voltage 115VAC, 50/60Hz, 1.9A

Outputs

Voltage 6 - 15VDC
Current 10A total output current
Protection Fused 3.5A / PTC 2.5A

Indicators (LED)

Output Sixteen (16) individual LEDs

Agency Listings

CE European Conformity

Physical and Environmental

2U rack mount chassis for use in standard EIA 19" rack.

Dimensions (H x W x D):

Enclosure: 3.26" x 19.125" x 8.5" (83mm x 486mm x 216mm)
Shipping: 20.25" x 12.5" x 7.25" (514.4mm x 317.5mm x 184.2mm)

Weight (approx.):

Product: 17.15 lb. (7.78 kg)
Shipping: 18.15 lb. (8.23 kg)

Temperature

Operating: 0°C to 49°C (32°F to 120°F)
Storage: - 20°C to 70°C (- 4°F to 158°F)

Relative Humidity 85% +/- 5%

BTU/Hr. (approx.): 46-77 BTU/Hr.

Lifetime Warranty