



ALTV244175ULCB3

**Overview**

ALTV244175ULCB3 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) Class 2 Rated PTC protected power-limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

**Specifications****Input:**

- 115VAC, 50/60Hz, 1.76 amp.

**Output:**

- Four (4) PTC protected outputs.
- 24VAC @ 7 amp (170VA) supply current  
(1.75 amp per device, 2.5 amp max.)  
or 28VAC @ 6.25 amp (175VA) supply current  
(1.56 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 85.99 BTU/Hr.
  - 28VAC: 89.57 BTU/Hr.

**Electrical (cont'd):**

- System AC input VA requirement: 202.4VA.

**Features:**

- Secondary fuse rated @ 10 amp/250V.
- Factory installed 3-wire line cord.
- AC power LED.
- Power ON/OFF switch.

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.):  
12.25" x 7.5" x 4.5" (311mm x 184mm x 114mm)
- Product weight (approx.): 10.8 Lbs (4.9 kg)
- Shipping weight (approx.): 11.8 Lbs (5.4 kg)

**Agency Approvals**

UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

**Enclosure Dimensions (H x W x D approximate):**  
 12.25" x 7.5" x 4.5" (311mm x 184mm x 114mm)

