

SLA-T4680D/T4680DW/T4680DS

2M Door Jamb Lens Modules



SLA-T4680D
(black)



SLA-T4680DW
(white)



SLA-T4680DS
(silver)

Key Features

- Compatible with XNB-6001
- Max. 2Megapixel (1920 x 1080) resolution
- 4.6mm pinhole lens
- 0.06Lux@F2.5
- 8m cable
- Easy installation
- Flexible panning ± 30 degrees
- Multiple housing color options to match the door jamb
- Hidden security screw for discrete look

SLA-T4680D		SLA-T4680DW		SLA-T4680DS	
VIDEO					
Imaging Device		1/2.8" 2M CMOS			
Total Pixels		1,945(H) x 1,109(V) 2.16M			
Effective Pixels		1,945(H) x 1,097(V) 2.13M			
Scanning System		Progressive Scan			
Min. Illumination		Color : 0.06Lux (F2.5) B/W: 0.06Lux (F2.5)			
S / N Ratio		50dB			
Wide Dynamic Range		120dB			
Day & Night		Electrical			
LENS					
Focal Length (Zoom Ratio)		4.6mm			
Max. Aperture		F2.5			
Angular Field of		H : 73° / V : 39° / D : 85°			
Min. Object Distance		0.98ft (0.3m)			
Lens Type		Pinhole			
Mount Type		RJ12 connected with main unit			
ENVIRONMENTAL					
Operating Temperature / Humidity		-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH			
Storage Temperature / Humidity		-50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH			
MECHANICAL					
Color / Material	Lens	Black / Plastic	Black / Plastic	Black / Plastic	
	Cable	Black	Black	Black	
	Housing	Black	White	Silver	
Dimensions (WxHxD)	Lens	Ø0.94" x 1.65" (Ø24 x 42mm)			
	Cable	314.96" (8m)			
Weight		0.68 lb (310g)			

* The latest product information / specification can be found at hanwha-security.com
 * Design and specifications are subject to change without notice.
 * Wisenet is the proprietary brand of **Hanwha Techwin**, formerly known as Samsung Techwin.

Dimensions

Unit: inch (mm)

