

SLA-2M2400D/2800D/3600D/6000D

2MP Optional Lenses for PNM-7000VD



SLA-2M2400D



SLA-2M2800D



SLA-2M3600D



SLA-2M6000D

Key Features

- 0.055Lux@F2.0 (Color, B/W)
- WDR (150dB)
- 2.4mm fixed lens (SLA-2M2400D)
- 2.8mm fixed lens (SLA-2M2800D)
- 3.6mm fixed lens (SLA-2M3600D)
- 6.0mm fixed lens (SLA-2M6000D)

	SLA-2M2400D	SLA-2M2800D	SLA-2M3600D	SLA-2M6000D
VIDEO				
Imaging Device	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS	1/2.8" 2M CMOS
Total Pixels	1,945(H) x 1,109(V) 2.16M	1,945(H) x 1,109(V) 2.16M	1,945(H) x 1,109(V) 2.16M	1,945(H) x 1,109(V) 2.16M
Effective Pixels	1,945(H) x 1,097(V) 2.13M	1,945(H) x 1,097(V) 2.13M	1,945(H) x 1,097(V) 2.13M	1,945(H) x 1,097(V) 2.13M
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan	Progressive Scan
Min. Illumination	Color : 0.055Lux (F2.0) B/W : 0.055Lux (F2.0)	Color : 0.055Lux (F2.0) B/W : 0.055Lux (F2.0)	Color : 0.055Lux (F2.0) B/W : 0.055Lux (F2.0)	Color : 0.055Lux (F2.0) B/W : 0.055Lux (F2.0)
S / N Ratio	50dB	50dB	50dB	50dB
Wide Dynamic Range	150dB	150dB	150dB	150dB
Day & Night	Electrical	Electrical	Electrical	Electrical
LENS				
Focal Length (Zoom Ratio)	2.4mm	2.8mm	3.6mm	6.0mm
Max. Aperture Ratio	F2.0	F2.0	F2.0	F2.0
Angular Field of View	H : 135.4°, V : 71.2°, D : 161.6°	H : 107.4°, V : 62.2°, D : 122.0°	H : 94.8°, V : 49.3°, D : 114.3°	H : 50.4°, V : 28.8°, D : 58.1°
Lens Type	Fixed focal	Fixed focal	Fixed focal	Fixed focal
MECHANICAL				
Color / Material	Black / Plastic	Black / Plastic	Black / Plastic	Black / Plastic
Dimensions (WxHxD)	Ø35.5 x 27.9mm (1.4" x 1.1")	Ø35.5 x 27.9mm (1.4" x 1.1")	Ø35.5 x 27.9mm (1.4" x 1.1")	Ø35.5 x 27.9mm (1.4" x 1.1")
Weight	27g (0.06 lb)	27g (0.06 lb)	27g (0.06 lb)	27g (0.06 lb)

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of **Hanwha Techwin**, formerly known as Samsung Techwin.

Dimensions

Unit: mm (inch)

