

AXIS Camera Station S2224 Appliance

All-in-one recorder with PoE switch for UHD surveillance

AXIS Camera Station S2224 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2224 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 24 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 5-year warranty, AXIS S2224 provides a reliable surveillance solution.

- > **All-in-one solution with integrated PoE switch**
- > **High-definition surveillance with up to 4K resolution**
- > **AXIS Camera Station licenses included**
- > **Full compatibility with Axis products**



AXIS Camera Station S2224 Appliance

Licenses	24 AXIS Camera Station core licenses included and tied to the hardware. Can be upgraded with additional licenses (sold separately).	4 split x 1080p Up to 24 cameras split view Supports two monitors, maximum one 4K monitor recommended
System scalability	Qualified for up to 24 video channels and 48 doors	Playback: Supports the same split scenarios as live view Supports only one monitor
Hardware		
Processor	Intel® Core™ i5	Recording Qualified for recording up to 24 video channels with a total recording rate up to 384 Mbit per second
Memory	8 GB	General Operating system Microsoft® Windows® 10 IoT Enterprise SAC Operating system recovery: yes Operating system drive: 120 GB SSD
Storage	Surveillance Class HDD Total HDD slot: 4 Free HDD slot: 2 Out-of-the-box storage: 12 TB (2x6 TB)	
RAID	RAID levels: 0, 1, 10	Operating conditions 0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing)
Switch	24 ports integrated, 260 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4	Storage conditions -40 °C to 65 °C (-40 °F to 149 °F)
Graphic card	Intel® HD Graphics	Approvals EMC CNS 13438, EAC, EN 55024, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1, IS 13252
Power	Max 520 W, 260 W PoE dedicated 100 – 240 V AC, 6.5-2.5 A, 50/60 Hz	Dimensions 476 x 440 x 45 mm (18.7 x 17.3 x 1.8 in), 1U chassis
Connectors	Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: 24x PoE ports 10/100 Mbps 1x SFP 10/100/1000 Mbps 1x RJ45 10/100/1000 Mbps Rear side Server: 1x RJ45 10/100/1000 Mbps 2x USB 2.0 1x Displayport™ 1x HDMI port	Weight 11 kg (24.3 lb) Included accessories Rack rails, power cord Optional accessories Surveillance Hard Drive 6 TB available from Axis Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com Warranty Recorder and hard drive: 5-year warranty, see axis.com/warranty
Video		
Video streaming	Live view: Surveillance	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility