FIO Selles SO4SZXANN		
Electrical		
Power Supply	24 VDC, 2.5 A; PoE+ (IEEE802.3at Class 4)	
Power Consumption	Basic: 10 W Maximum: 16 W	
Environmental		
Operating Conditions	-40° C to 60° C (-40° F to 140° F), Less than 95% RH	
Ingress Protection	IP67	
Vandal Resistance	IK10	
Surge Protection	6 KV, lightning proof; surge protection; voltage transient protection	
Construction		
Casing	Metal	
Dimensions	ø186.0 mm x 253.0 mm (ø7.32 in. x 9.96 in.)	
Net Weight	2.50 kg (5.51 lb)	
Gross Weight	4.50 kg (9.92 lb)	
Analytics+ Functions		
Perimeter Protection	Detects human or vehicle violations using the following methods: Tripwire: a target crosses a defined line. Intrusion: a target enters or exits a defined perimeter. Monitors a combination of ten (10) detection methods. Search and retrieve video based on target type.	
Face Detection	Detects and captures a snapshot of a human face within a scene.	
Smart Motion Detection+	 Differentiates between and classifies human and vehicle objects. Filters false alarms due to leaves, lights, animals, and other inconsequential objects. 	

ligence

IVS triggers an alarm and takes a defined action for the following events:

Standard Features	 Tampering with the camera. Error writing to an onboard Micro SD card. Error sending or receiving data over the network. Unauthorized access to the camera. 	
Premium Features		
Motion	An object moves through any part of the scene.	
Scene Change	A person or object moves the camera to change the scene or covers the camera to obscure the scene.	
Abandoned/Missing Object	A target leaves an object in designated area, or a target removes an object from the same designated area.	
Advanced Features		
Auto-track	Controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene.	

other inconsequential objects.

for quick target search and retrieval.

• Extracts human or vehicle objects from recorded video

Туре	Part Number	Description
4 MP PTZ Camera	50432XANR	4 MP 32x Starlight PTZ Network Camera, True WDR, Analytics+
]	DC24V/2.5A	Power Adapter
Accessories, princluded	PFA110	Mount Adapter
	PFB300S	Wall Mount (use with PFA110 mount adapter)
	PFA110-N	Mount Adapter (NPT 1-1/2 in.)
ŀ	PFA120	Water-proof Junction Box
ŀ	PFA140	Power Box
1	DH-PFA143	Outdoor Surveillance Junction Box
	PFA150	Pole Mount
Accessories, optional	PFA151	Corner Mount
1	DH-PFA153	Heavy-duty Pole Mount Bracket
ſ	PFB300C	Ceiling Mount (use with PFA110 mount adapter)
I	PFB303S	Parapet Mount (use with PFA110 mount adapter
F	PC-H84.5-147	Polycarbonate Smoke Tinted Bubble

Accessories

Included:



PFB300S Wall Mount Optional:



PFA110 Mount Adapter



DC24V/2.5A Power Adapter

PFA140 Power Box



PFB300C Ceiling Mount





PFA120 Junction Box



PFA151 Corner Mount





PFB303S Parapet Mount



PFA150

Pole Mount

DH-PFA143 Outdoor Surveillance Junction Box



DH-PFA153 Heavy Duty Pole Mount Bracket



PC-H84.5-147 Polycarbonate Smoke Tinted Bubble

