



TDS-16489U-SF2-R2 (Legacy)

CPU	E5-2630 v4 10-core 2.2 GHz processor x2
-----	---

CPU Architecture	64-bit x86
------------------	------------

Floating Point Unit	Yes
---------------------	-----

Encryption Engine	Yes (AES-NI)
-------------------	--------------

Hardware-accelerated Transcoding	QTS: Optional via a PCIe graphics card QES: N/A
----------------------------------	--

System Memory	128GB RDIMM DDR4 (8 x 16GB)
---------------	-----------------------------

Maximum Memory	RDIMM/LRDIMM: 1 TB (16 x 64 GB)
----------------	---------------------------------

Memory Slot	16 x RDIMM DDR4
-------------	-----------------

Flash Memory	4GB (DOM for dual OS)
--------------	-----------------------

Drive Bay	Front: 16 x 3.5-inch Rear: 4 x 2.5-inch
-----------	--

Drive Compatibility	3.5-inch bays: 3.5-inch SATA/SAS hard disk drives 2.5-inch SATA/SAS hard disk drives 2.5-inch SATA/SAS solid state drives 2.5-inch bays: 2.5-inch SATA/SAS solid state drives
---------------------	--

Hot-swappable	Yes
---------------	-----

SSD Cache Acceleration Support	Yes
--------------------------------	-----

GPU pass-through	Yes
------------------	-----

SR-IOV	Yes
--------	-----

Gigabit Ethernet Port (RJ45)	2
------------------------------	---

10 Gigabit Ethernet Port	4 x 10GbE SFP+
--------------------------	----------------

Wake on LAN (WOL)	Yes
-------------------	-----

Jumbo Frame	Yes
PCIe Slot	4 Slot 1: PCIe Gen 3 x16 Slot 2: PCIe Gen 3 x8 Slot 3: PCIe Gen 3 x8 Slot 4: PCIe Gen 3 x8
USB 3.2 Gen 1 port	4
IPMI	3 (LAN, VGA, console) *Only work with QTS OS
Form Factor	3U Rackmount
LED Indicators	HDD 1-16, Status, 10 GbE, LAN, storage expansion port status
Buttons	Power, Reset
Dimensions (HxWxD)	5.15 × 17.48 × 29.29 inch
Weight (Net)	49.43 lbs
Weight (Gross)	66.56 lbs
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	Redundant/ Hot Swap ATX Power Supply,Input: 50-60 Hz 100-127V~/ 10A 200-240V/ 5A Output: 770W
Power Consumption: HDD Sleep Mode	254.21 W
Power Consumption: Operating Mode, Typical	362.86 W
Fan	4 x 60mm, 12VDC
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	10000

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.