



Summary

This MEGAPIX® IVA™ IP camera is your gateway to powerful video analytics features. It is NDAA/TAA compliant and provides 5MP resolution at real-time 30fps. The MEGAPIX IVA cameras have a powerful engine to detect and classify people and vehicles in real-time. IVA+ license upgrade offers advanced Video Content Analysis detection capabilities. This camera includes a 2.7-13.5mm vari-focal auto-focus lens with motorized zoom, simultaneous H.265/H.264/MJPEG codec support and Star-Light Plus™ color in near-total darkness technology for quality video in any lighting condition. The IP66-rated, IK-10 impact resistant vandal housing features CleanView™ self-cleaning dome treatment. All MEGAPIX® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 5MP 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Intelligent Video Analytics (IVA)
- Extended Intelligent Video Analytics (IVA+ license required)
- 2.7-13.5mm vari-focal p-iris lens with motorized zoom and auto-focus
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- CleanView™ hydrophobic dome coating repels water, dust and grease
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- Two-way audio
- Micro SD/SDHC/SDXC class 10 card slot (card not included)
- Alarm sensor input and relay output
- Web server built-in
- PoE class 3 and DC12V
- NDAA/TAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- IK 10-rated impact-resistant
- 5 year warranty



Accessories (Optional)



DWC-V1CNMW
Corner mount



DWC-VFJUNCW
Junction box




DWC-VFCMW
Ceiling mount bracket



DWC-VFWMW
Wall mount bracket

Dimensions

Unit: Inch (mm)



Specifications

IMAGE	
Image sensor	5MP 1/2.8" CMOS
Total pixels	2592(H) X 1944(V)
Minimum scene illumination	0.08 lux (color) 0.0 lux (B/W)
Video output	Local video output CVBS 1.0V p-p (75Ω), 4:3 aspect ratio
LENS	
Focal length	2.7-13.5mm, F1.4
Lens type	Vari-focal p-iris lens with motorized-zoom and auto-focus
HFOV / VFOV	96° - 31° / 70° - 24°
IR distance	100ft range
Optical zoom / digital zoom	x5 optical zoom
I/O	
Audio in/out and compression	1/1
Audio compression	G.711
Alarm in/out	1/1
OPERATIONAL	
Intelligent Video Analytics	IVA license: intrusion, line crossing, counting line, loitering, enter, exit, tamper IVA+ license: object removed, tailgating, direction, stopped, appear, disappear, object left
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15 - 1/32000
Slow shutter	1/2, 1/3, 1/5, 1/6, 1/7, 5, 1/10
Auto gain control	Auto
Day and night	Auto, day (color), night (B/W)
Smart DNR™ 3D digital noise reduction	3D-DNR
Wide Dynamic Range (WDR)	True WDR, 120dB
Privacy zone	16 programmable privacy masks
Backlight Compensation (BLC)	Yes
Mirror and flip	Yes
Alarm notifications	Notifications via e-mail notifications, FTP, alarm output and SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
NETWORK	
LAN	10/100 Base-T
Video compression type	H.265, H.264, MJPEG
Resolution	H.265: 2592x1944, 2304x1296, 21MP/1080p, 720p, VGA, D1, CIF H.264: 2592x1944, 2304x1296, 21MP/1080p, 720p, VGA, D1, CIF MJPEG: 21MP/1080p, 720p, 800x600, VGA, 768x432, D1, CIF
Frame rate	Up to 30fps at all resolutions
Video bitrate	H.264 / H.265: 32Kbps - 14Mbps MJPEG: 1Mbps - 40Mbps
Bitrate control	Multi-streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari®
Video management software	DW Spectrum® IPVMS
ENVIRONMENTAL	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	10-90% RH (non-condensing)
IP and IK rating	IP66-rated, IK10 impact resistant
Other certifications	CE, FCC, RoHS
ELECTRICAL	
Power requirement	DC 12V, PoE IEEE 802.3af Class3. (Adapter not included)
Power consumption	DC12V: max7.4W PoE: max8.7W
MECHANICAL	
Material	Aluminum vandal housing, polycarbonate dome
Dimensions	4.9" x 3.6" (125 x 92 mm)
Weight	1.12 lb (0.51kg)
Warranty	5 year warranty