

8+2 100Mbps PoE Switch

POE-0802M



Overview:

AI1010 is a 10-port PoE switch. It has 4 working modes, AI VLAN mode, AI Extend mode, AI PoE mode, AI QoS mode. All ports are free to communicate by default; In AI VLAN mode, 1-8 ports are isolated from each other, which can effectively restrain network storms and improve network performance. In AI Extend mode, the effective transmission distance of 1-8 ports can reach 250 meters, which is suitable for remote monitoring and power supply. In the AI PoE mode, the switch automatically detects the working status of the PD device and finds that the device abnormal automatically restarts the device. In AI QoS mode, the video data will be processed preferentially when the device is congested to make the video smoother.

The device supports IEEE 802 af/at standard, which can automatically detect and identify the PDs that comply with the IEEE 802 af/at standard and provide power for them, so there is no need to worry about PoE or non-PoE devices that can damage private standards.

Key Features

AI Extend: 1-8 port supports 250M meters long distance power supply (recommended cat 5 or above)

AI VLAN: Isolating ports 1-8 from each other, restrain network storms effectively and improve network performance.

AI QoS: Customize application prioritization and increase network sensitivity. For example, video priority, monitoring transmission more smoothly

AI PoE: Automatic detection power of port, power off and restart the device if find dead machine.

Supports IEEE 802.3af/at standard, automatically detects and identifies devices that comply with the IEEE 802.3af/at standard and supply power to it

Support Auto MDI/MDIX.

Adopt store-and-forward exchange method.

Intelligent power supply, the lowest power consumption, ensure PD power needs.

With power circuit protection, protect the safety of PD.

No configuration characteristics of the power supply is automatically supplied to the adaptive equipment.

Fanless design, energy saving and environmental protection; no noise, reduce the impact on the environment

Compact size design

Support port without link power saving function

All ports have wire-speed forwarding capability.

Plug and play, easy to use.

Caution

1. In order to safety, please non-professionals don't open the casing of product;
2. Please be careful the risk of strong current and security protection when products carry power;
3. Please select the right power adaptor provide power for PoE switch, before using please confirm if is it accord with the requirement of PoE switch;
4. Please don't use PoE switch under the humid environment, avoiding water go into the product inside caused PoE switch breakdown.
5. Please start the power after the circuit connected;
6. Please don't plug-in and plug-out the connection cable when product is carrying on power;
7. Please don't use PoE switch under somewhere with more dust and EME;
8. Please don't put heavy thing on PoE switch, in order to having an accident.;
9. According to the IEEE802.3af/at standard, please use the Cat5 or above, transmission distance 250 m;
10. Please don't exceed the maximum output power of PoE switch when it connect more than one PD device;
11. Suggestion that PoE switch use for indoor, if you want to use for outdoor, please install waterproof box

Technical Specification

Port	· 8 10/100Mbps PoE RJ45 port (port 1~port 8)
	· 2 10/100Mbps non-POE RJ45 port(port 9~port 10)
Transfer Rate	·100Mbps full Duplex, 10 or100Mbps Half Duplex
Standard	·IEEE802.3i, IEEE802.3u, IEEE802.3x, IEEE802.3af IEEE802.3at
Performance	·Bandwidth: 2Gbps(no block)
	·Network delay(100 to100Mbps): maximum 20 μs (using 64 byte packet)
	·Frame filtering and transmission rate:
	10M port maximum 14,800pps,100M port maximum 148,800pps
	Support 1K MAC address
	Packet forwarding rate:1.48Mpps
LED indicator	·Power
	·LINK/ACT
POE Pin	1/2(+), 3/6(-)
Power	·Max power single port: 30W
	·External power adapter: 120W
Dimensions	·Size (LxWxH): 184mm*94mm*27mm
	·Weight: 0.95kg,(2.1lb)
Input power	·DC 52V
Environment	·Operating Temperature: 0°~40°C (32°F-104°F)
	·Operating Humidity:: 10%~90%, Non-condensing
Certifications	·CE/ROHS/FCC