

## GV-Access Card, Key Fob, Tag, Sticker, Mobile Card



GeoVision offers a wide range of access cards, key fobs, stickers, and tags to satisfy your needs. **GV-AS ID Card** is suitable for use in commercial environments where identification and access control are critical for security. **GV-AS ID Key Fob** and **GV-Tag Sticker** are perfect for home applications since they are intended for simple carrying and key replacement. **GV-UHF Tag** is ideal for managing parking lots. **GV-Patrol Fob** is excellent for patrol stations with high mobility that may be quickly deployed.

In addition, we offer the virtual access card **GV-Mobile Card**, which is used with the QR code reader GV-QR1352 and the GV-Mobile Access app to unlock doors with smartphones.

### KEY FEATURES

- 125 KHz cards and key fobs
- 900 MHz ISO 18000-6C UHF RFID tags
- 13.56 MHz ISO 14443A cards, key fobs, patrol fobs, and stickers
- 13.56 MHz Mifare DesFire cards
- Virtual access cards

| Model Name                           | Frequency           | Compatible Devices                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GV-AS ID Card / GV-AS ID Key Fob     | 125 KHz             | <b>GV-Reader:</b> <a href="#">GV-DES1352</a> / <a href="#">GV-SR1251</a> / <a href="#">GV-QR1352</a><br><b>GV-Enrollment Reader:</b> <a href="#">GV-PCR1251</a>                                                                                                                                                                                                                                                                                     |
| GV-AS ID Card / GV-AS ID Key Fob     | 13.56 MHz           | <b>GV-AS Controller:</b> <a href="#">GV-AS1010</a> / <a href="#">GV-CS1320</a><br><b>GV-Reader:</b> <a href="#">GV-CR1320</a> / <a href="#">GV-DES1352</a> / <a href="#">GV-DFR1352</a> / <a href="#">GV-FR2020</a> / <a href="#">GV-R1352</a> / <a href="#">GV-RK1352</a> / <a href="#">GV-QR1352</a> / <a href="#">GV-RKD1352</a> / <a href="#">GV-R1355</a> / <a href="#">GV-RKR1355</a> / <a href="#">GV-RKV1355</a> / <a href="#">GV-R1354</a> |
| GV-AS ID F Card / GV-AS ID F Key Fob |                     | <b>GV-FR Panel:</b> <a href="#">GV-FR Panel</a><br><b>GV-GF Fingerprint Reader</b> (Card Only Mode): <a href="#">GV-GF1922</a>                                                                                                                                                                                                                                                                                                                      |
| GV-Patrol Fob                        |                     | <b>GV-Enrollment Reader:</b> <a href="#">GV-PCR1352</a>                                                                                                                                                                                                                                                                                                                                                                                             |
| GV-Tag Sticker                       |                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| GV-UHF Tag                           | 900 MHz             | <b>GV-AS Controller:</b> <a href="#">GV-AS1520</a><br><b>GV-UHF Reader:</b> <a href="#">GV-RU9003</a>                                                                                                                                                                                                                                                                                                                                               |
| GV-Mobile Card                       | Virtual Access Card | <b>GV-QR Code Reader:</b> <a href="#">GV-QR1352</a>                                                                                                                                                                                                                                                                                                                                                                                                 |

| Model Name                            | Dimensions                   | Operating Temperature    |
|---------------------------------------|------------------------------|--------------------------|
| GV-AS ID Card & GV-AS ID F Card       | 85.5 x 54 mm (3.4" x 2.1")   | -20 ~ 70°C (-4 ~ 158°F)  |
| GV-AS ID Key Fob & GV-AS ID F Key Fob | 30.5 x 37.5 mm (1.2" x 1.5") | -20 ~ 55°C (-4 ~ 131°F)  |
| GV-Patrol Fob                         | 34 x 6 mm (1.3" x 0.2")      | -45 ~ 85°C (-49 ~ 185°F) |
| GV-UHF Tag                            | 97 x 12 mm (3.8" x 0.5")     | -20 ~ 85°C (-4 ~ 185°F)  |
| GV-Tag Sticker                        | Ø 25 mm (Ø 0.98")            | 0 ~ 50°C (32 ~ 122°F)    |

**Note:** The hole option of the GV-AS ID Card is only available for 13.56 MHz ISO 1444-3A.