

## N8WA4

8 Channel Facial Recognition Wall Mount NVR with 8 Built-in PoE Ports

I-VIEW NOW *immix*



### Configurations

N8WA42TB	N8WA46TB	N8WA412TB
N8WA44TB	N8WA48TB	N8WA416TB

### N8WNRE Key Features


#### EZ Wizards - For ease of use and setup

- Camera:** quickly discover and install all Speco IP cameras
- Setup:** for quick setup of general settings
- Network:** network setup and port forwarding
- Record:** quickly setup recording resolutions and recording type
- EZ Search 2.0:** Quickly find an event using time-sliced thumbnail images of your recordings with quick preview
- Copy:** quickly copy what you are playing onto a USB flash drive

#### EZ Mobile - easy mobile setup for viewing on desktop or mobile apps

- Real time recording up to 8MP resolution (4K) at 30fps
- H.265 compression - Store up to 2x more than H.264!
- 4K HDMI out and one VGA monitor output,
- N8WNRE: 1 SATA port for up to 16TB of storage max
- Facial Recognition and Comparison\*\*
- Human and vehicle detection\*
- Object and line crossing detection and alerts\*
- Smart Search - Specify a region on the camera view and search on changes in that area\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- Remote control included

\*with Speco Smart Analytic Cameras  
\*\*with Speco Facial Recognition Cameras



N8WA4 shown



### Additional Features

- Find and install IP cameras on the local network without needing to locate the cameras manually
- Supports different recording types: Continuous, Motion, Analytics, and Sensor
- Create bookmark pins on playback for easy reference
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the internet
- Simultaneous HDMI & VGA video output (N8WNRE)
- Supports 2-way audio communication (speaker required)

INTEGRATED WITH **speco access**



- Auto Live Camera Pop-Up
- View A Camera
- Event Tag



1Limited Warranty/Hard drives excluded. Check www.specotech.com for more details. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/1/22

Apps available from the following:



Video	Input	Max. IP Channels	8
		IP Camera	H.264/H.265 Auto Detection (Max. 8MP)
	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)
Audio	Network Input		8 Ch. IPC audio input
	2-way Audio		RCAx1
	Local Output		RCAx1
Recording	Encoding Resolutions		8MP/5MP/4MP/3MP/1080P/720P
	Codec		H.264/H.265 (Auto Detection)
	Max Frame Rate per Channel		Any Resolution @30fps
	Recording Mode		Analytics/Continuous/Motion/Sensor/Schedule/Manual
	Pre-Recording		Max. 5 seconds
	Post Recording		Max. 10 minutes
Search & Playback	Search		EZ Search, Motion, Specific Date/Time, Event, Museum, Bookmarks, Snapshots, Log
	Simultaneous Playback		Max. 8 Ch.
	Smart Search		Highlighted color to display camera records in a certain period of time, different colors refer to different record events
	Playback Resolutions		8MP/5MP/4MP/3MP/1080P/720P
	Playback Functions		Play, pause, FF, FB, digital zoom, etc.
Backup	Media		USB drive, Network
	Format		JPG, AVI, ZIP (Player+Proprietary Data)
Storage	HDD	Max Capacity of each HDD	16TB
		Internal SATA ports	1
	USB	Front	1 USB 2.0
		Rear	1 USB 3.0
Alarm	Mode		Manual, sensor, motion, exception, intelligence
	Input		8 Ch. local
	Output		4 Ch. local
	Linkage		Record/Snapshot/Preset/Email/Pop-up Window
User I/F	Input Method		IR Remote, Mouse
Network	Network Bandwidth		80Mbps
	P2P/Dynamic DNS		Free US-Based Speco P2P and DDNS Service
	Network Protocols		TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP
	LAN 1		Recorder
Network Access	Mobile		iOS/Android via Speco Blue App, SecureGuard® Client
	Other Viewing Platforms		Apple TV and Amazon Fire TV
	Web Viewer		Windows IE
	VMS/CMS		SecureGuard®
	Max. User Access		Max 10 users online (web client)
Features	Digital Zoom		Live and Playback, Free Size
	Smart Analysis		* **Facial Recognition, Crowd Density, People Counting, Object Detection, Tampering, Tripwire, Intrusion
	S.M.A.R.T		Temperature, Power On Time, Bad Sectors and Health
Power	Power Consumption		≤ 15W (without HDD)
Environment	Operating Temperature		-4°F ~ 122°F(-10°C ~ 50°C)
	Operating Humidity		10% ~ 90% humidity
Dimensions	Unit		387mm x 298mm x 89mm (15.25" x 11.75" x 3.5")

\* Does not have built in DHCP server

Please note that specifications and unit exterior design are subject to change without notification. Rev. 2/1/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com



# Wall Mount Containing 4K H.265 NVR with Facial Recognition and Smart Analytics & 4-door Access Controller with NVR Integration

## A2E4 & A2M Features

- Embedded Linux operating system
- 4 Readers (In/Out)
- 4 Relays (Lock/Aux)
- 6 Inputs (REX, DPS, Aux) Global

Specifications	
Processor	Quad Core Cortex, 1.5 GHz
Memory	1 GB DDR3 & 8GB eMMC
Operating System	Embedded Linux
Transactions	> 45 per second
Operating Temperature	50°F to 95°F (10°C to 35°C)
Battery Backup	Controllers & Readers
Recommended Battery Type (battery is not included)	Powersonic PS-1270-FI or Similar 12V, 7AH, Sealed Lead Acid with 0.187 inch terminals
Standby Power Requirement	450mA @ 12V
Readers (Wiegand)	8 Total, One In & One Out Reader for Each Door
Reader Power	300mA @ 12V Max per Reader 1000mA @ 12V Max per System
Request to Exit (REX) Inputs	4 Total, One for Each Door
Door Position (status) Inputs	4 Total, One for Each Door
Auxiliary Input	4 Total, General Purpose
Power Fault Digital Input	Yes, Prewired on Units with Integrated Power
Door Lock Outputs	2 Form C Relay, 24V @ 2.0A
Auxiliary Outputs	2 Form C Relay, 24V @ 2.0A

## P4S5G Features

- Gigabit performance on all ports (uplink and downlink)
- CCTV mode isolates each port from one another for added security and performance
- Includes built-in surge immunity

Specifications	
Downlink Ports	4 x 10/100/1000 Base-T (PoE)
Uplink Ports	1 x 10 / 100/1000 Base-T
Network Standards	IEEE 802.3/IEEE803.2u/IEEE802.3ab/ IEEE802.3x
PoE Standards	802.3af/at (PSE)
Switch Capacity	10GBps
Packet Forwarding Rate	7.44Mpps
Exchange Type	Storage & Forwarding
MAC Address List	2K
PoE Power Supply	1/2(+), 3/6(-)
PoE Output	Single port ≤ 30W (54V DC), Total for all ports ≤ 60W
Surge Immunity	6KV : IEC61000-4-5
ESD Protection	Contact discharge 6K, Air discharge 8KV, Per: IEC61000-4-2
Voltage Input	DC 48V ~ 57V
Power Consumption	5W
Operation Temperature	14°F to 131°F (-10°C to 55°C)
Storage Temperature	-40°F to 185°F (-40°C to 85°C)
Operation Humidity	5% - 95% (Non-condensing)

Please note that specifications and unit exterior design are subject to change without notification. Rev. 2/1/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • [specotech.com](http://specotech.com)

