

# 6.5" 25/70V In-Ceiling Speaker

## SPG6MT

### Features

- Magnetic grille for quick and easy installations
- 70 or 25V transformer with settings up to 5W
- NDAA compliant
- Optional back can for protection and improved sound:  
SPG6MTCAN (Sold separately)
- Sold each



Specifications	SPG6MT
RMS Power	15W
Max Output Power	22.5W
Transformer Type	70/25V
Transformer Power Taps	5, 2.5, 1W
Termination Type	Colored leads
Sensitivity (1W/1M)	86dB
Maximum SPL (Pmax/1M)	93dB
Driver Impedance	8 Ohms
Magnet	8 oz. Ferrite
Frequency Response Range	70Hz ~ 20kHz
Dispersion @ 1000Hz	150 degrees
Drivers	6.5" Polypropylene Woofer 0.5" Mylar Dome Tweeter
Speaker Dimensions	9.25" (Dia.) x 3.74" D
Mounting Dimensions	8" (Dia.) x 3.5" D
Weight	2.9 lbs.
Material	Baffle: ABS Grille: Steel
Color	White Grille, Black baffle



**NDAA**  
COMPLIANT

### Optional Accessories



BRC6F  
Tile Bracket  
sold in pairs



SPG6MTCAN  
Back Can  
sold each

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/22/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • [specotech.com](http://specotech.com)

**speco technologies**