

4-Port HD-TVI Video Balun

TVIUTP4

Features

- HD-TVI Resolution up to 5MP
- HD-TVI Signal extension up to 820' (250M) over UTP CAT5e/6 depending on resolution and cable quality.
- Also supports AHD, HD-CVI, and standard analog
- Male BNC to terminal block design
- No power required
- Built-in ESD, EFT (impulse noise) and transient protection



Specifications

TVIUTP4

Support

Video Format	HD-TVI, AHD, HDCVI, CVBS
Max. Transmission Distance	5MP
HD-TVI Transmission Distance	Up to 820' (250M)@2MP
Bandwidth	50Hz to 60MHz (-3dB)

Ports & Interfaces

Video Input/ Output	4 x BNC (1V p-p, 75Ω)
Link Interface	1 x 8-Pin Terminal (UTP), 1 x RJ45

Protection

ESD Protection	30 KV(Air), 15 KV (Contact), IEC 61000-4-2
EFT Protection	40A(5/50ns), IEC 61000-4-4
Lightning Protection	2A (8/20μs), IEC 61000-4-5
Response Time	<1 nS

Ambient Temperature

Operation	32 to 131 °F (0 to 55 °C)
Storage	-4 to 185 °F (-20 to 85 °C)
Humidity	Up to 95%

Physical Characteristics

Dimensions	4.3 x 3.2 x 1" (110 x 80.6 x 26.3mm)
Weight	0.4 lbs (195g)

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/14/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

