

IP In-Ceiling Speaker

SPIPG86TG

8" Classic Grille In-Ceiling Speaker

Features

- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- PoE or 12/24VDC
- Two-way audio support with mic input




Network Specifications

Security	Password protection, IP address filtering, digest authentication, user access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support for SIP protocol for integration with VoIP systems, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier Description	Built-in 15W Amplifier
-----------------------	------------------------


Diagram



Specifications

RMS Power	10W
Max. Power	15W
Maximum SPL (Pax/1M)	90dB
Driver Impedance	8 Ohms
Frequency Response Range	85Hz - 18kHz
Dispersion @ 1000Hz	120° Conical
Driver	8" paper cone woofer, 0.8" dual cone tweeter
Speaker Dimensions	13" (Dia.) x 3.5" (D)
Mounting Dimensions	11.3" (Dia.)
Minimum Mounting Depth	2.7"
Weight	2.7 lbs.
Material	Grille: steel
Color	Off-White

Optional Accessories



TS8
T-Bar Bridge for
Ceiling Support



STH8
Heavy Gauge
Steel Backcan