

EN1215 Series Universal Transmitters

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Programmable as normally-open (NO) or normally-closed (NC)
- ▶ Small unobtrusive design
- ▶ Fully supervised
- ▶ Includes screw-closure housing, cover tamper, wall tamper
- ▶ Includes EOL resistor

These universal transmitters can make most normally-open (NO) or normally-closed (NC) sensors into wireless devices. The transmitters work with shock sensors, holdup buttons, pressure mats, temperature sensors, status relays, and other devices. They are designed for installations that require more security. They are fully supervised and include screw-closure housings, cover tampers, and wall tampers.

This line of universal transmitters includes:

- EN1215EOL Universal Transmitter with Wall Tamper and EOL Resistor
- EN1215WEOL Universal Transmitter with Wall Tamper, Reed Switch, and EOL Resistor

The Inovonics EchoStream platform uses diversity reception and advanced signal processing to reduce dead spots in transmission areas. The transmitters have superior range and reliability, and are ideally suited for commercial or residential installations.

System overview

Powered by Inovonics

The Inovonics EchoStream platform, powered by Inovonics wireless mesh network technology, ensures superior range, reliability, and scalability for commercial applications. Using a wide range of

transmitters and repeaters, this proven technology provides flexibility and performance to meet the most stringent requirements. This exclusive protocol is available only on Inovonics EchoStream products.

Wireless 900 MHz Band

The Inovonics EchoStream platform sends redundant information on several multi-frequency channels within the FCC Part 15 900 MHz band, providing superior range and reliability. In comparison, systems that use a single frequency technology can only send information on one narrow band channel. Any interference within the band can cause missed signals. With wireless registration, it is easy to add this technology to any application.

Functions

NO or N/C Operation

The universal transmitters work with any standard NO or NC contact (15 ms duration) or sensor.

Supervision

The cover tamper, wall tamper, and battery activity are supervised. Monitoring helps ensure reliable operation.

Wall Tamper and Cover Tamper

The wall tamper switch provides increased security and is ideal for high-end residential applications. The wall tamper switch notifies the system when the transmitter is removed from its mounted surface. The cover tamper switch notifies the system when an intruder attempts to remove the transmitter cover.

Design

The small, unobtrusive design of the transmitters makes them suitable for multiple design needs.

Certifications and approvals

Inovonics Wireless Corporation also holds the following approvals.

FCC Conforms to FCC Part 15 regulations

Installation/configuration notes

These universal transmitters are compatible with the following products:

Receivers

EN4016SK	Survey Receiver
EN4200	Serial receiver
EN4204R	LED Receiver

Repeater

EN5040-T	High-power Repeater
----------	---------------------

Parts included

EN1215EOL

Quant.	Component
1	Transmitter with screw-closure housing, cover tamper, and wall tamper
1	3.0 V lithium battery
1	2.2 kΩ EOL resistor
1	Mounting bracket
1	Hardware pack
1	Literature – Installation Instructions

EN1215WEOL

Quantity	Component
1	Transmitter with screw-closure housing, cover tamper, wall tamper, and magnetic reed switch
1	Magnet
1	2.2 kΩ EOL resistor
1	3.0 V lithium battery
1	Mounting bracket
1	Hardware pack
1	Literature – Installation Instructions

Technical specifications

Electrical

Power:	3.0 V, 1.4 Ah
Battery Replacement:	Duracell DL123A, Panasonic CR123A, or approved equivalent. Not all brands are equivalent. Use a specified brand.
Battery Life (Average):	3-5 years. Typical battery life shown assumes operating temperatures of +20°C to +30°C (+68°F to +86°F)

Environmental

Relative Humidity:	Up to 90%, non-condensing
Temperature (operating):	0°C to +60°C (+32°F to +140°F)

Mechanical

Dimensions:	8.9 cm x 4.3 cm x 2.3 cm (3.5 in. x 1.7 in. x 0.9 in.)
-------------	---

Transmission Characteristics

Frequency:	902 MHz to 928 MHz
------------	--------------------

Trademarks

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

Duracell is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Inovonics is a trademark of Inovonics Wireless Corporation.

Panasonic is a registered trademark of Matsushita Electric Industrial Co., Ltd.

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com